

MONARFLEX® SUPER T-PLUS

Commercial Product Data Sheet



USES: SITE ENCLOSURE

Color	Clear
Coverage	1000 sq ft (93 m ²) (less lap)
Thickness (at scrim)	16.5 mil (0.42 mm)
Roll Size	7'4" x 137' (2.2 m x 41.8 m)
Weight	54 lb (24 kg)

Properties	Value/Units	Test Method
Elongation	14.5%	ASTM D882
Tensile Strength*	MD 8571 psi TD 9988 psi	ASTM D882
Tear Strength	60 lb/force	N/A
Reinforcement	1670 Dtex	N/A
Eyelet Pullout Strength	190 lb/force	N/A
Light Transmission	85%	N/A
Thermal Stability	-40°F – 140°F (-40°C – 60°C)	N/A

*MD = Machine Direction
TD = Transverse Direction

PRODUCT INFORMATION

Application

Refer to the appropriate Siplast Installers Guide for detailed application information.

Storage and Handling

All Siplast Monarflex roll products should be stored horizontally on a clean, flat surface and stored in a dry place out of direct exposure to the elements. Materials stored on the job site during application should be kept on a pallet in a location that will protect the materials from rain or construction damage.

See product packaging and the Safety Data Sheet for specific information on the safe handling of this product.

Packaging

Sheeting Materials: Individually Wrapped Rolls
Rolls Per Crate: 30 of 7'4"