

PA-1125[®] ASPHALT PRIMER

Commercial Product Data Sheet



PA-1125 Primer is an asphalt/solvent blend designed to prime metal, concrete masonry, and other approved materials/surfaces prior to application of Siplast SBS Roofing and Flashing Systems.

Contact Siplast for information on approved product uses.

USES: ASPHALT PRIMER

Standards	ASTM D41
Unit	5 gal Pail 4.7 gal net content (17.8 L)
Coverage	Dependent on condition, profile, and porosity of surface receiving primer. Typical coverage ranges from 100 square feet per gallon (0.4 L per m ²) on very rough, porous surfaces to 400 square feet per gallon (1.6 L per m ²) on smooth, low-absorptive surfaces.
Flash Point	100°F (38°C) (Pensky-Martens Closed Cup)
VOC Content	>350 g/L

PRODUCT INFORMATION

Application

Refer to the applicable Siplast Technical Guide for detailed application information.



Storage and Handling

All Siplast priming products should be stored on a clean, flat surface. Care should be taken that containers are not dropped and container seals are not broken prior to use. All roofing products should be stored in a dry place out of direct exposure to the elements and kept away from excessive heat, fire, or open flames.

See product packaging and the Safety Data Sheet for specific information on the safe handling of this product.

Packaging

Pallet: 45 in x 48 in (114 cm x 122 cm) wooden pallet
 Pails Per Pallet: 42
 Pallets Per Truckload: 22
 Weight Per Pail: 37 lb (16.8 kg)

Listings, Approvals, & Certifications

