



PA-750[®] REINFORCING FABRIC

Commercial Product Data Sheet

PA-750[®] Reinforcing Fabric is a spunbonded polyester fabric reinforcement designed specifically for use with the PA-750 Hot-Applied Rubberized Waterproofing System.

Contact Siplast for information on approved product uses.

**USES:
PA-750 REINFORCEMENT**

Roll Length	Min: 1500 ft (457 m)
Roll Width	Avg: 36 in (0.9 m)
Thickness	10.4 mils (0.26 µm)

FABRIC PROPERTIES

Property (As Manufactured)	Value/Unit	Test Method
Sheet Grab Tensile (MD)	26 lb (129 N)	ASTM D4632
Sheet Grab Tensile (XD)	22 lb (96 N)	ASTM D4632
Sheet Trapezoid Tear (MD)	5.9 lb (26 N)	ASTM D1117
Sheet Trapezoid Tear (XD)	7.7 lb (34 N)	ASTM D1117
Unit Weight	1.35 oz/yd ² (46 gsm)	ASTM D3776
Textest Air Permeability	607 Cfm (308 cc/s/cm ²)	ASTM D737
Thickness	10.4 mils (0.26 microns)	ASTM D1777

PRODUCT INFORMATION

Application

Refer to the applicable Siplast Technical Guide for detailed application information.

Storage and Handling

All Siplast roll roofing products should be stored on end on a clean flat surface. Rolls should not be dropped on ends or edges or stored in a leaning position. Deformation resulting from these actions will make proper installation difficult. All roofing products should be stored in a dry place out of direct exposure to the elements and should not be double stacked. Material should be handled so that it remains dry prior to and during installation.

See product packaging and the Safety Data Sheet for specific information on the safe handling of this product.

Packaging

Rolls Per Pallet: 16
Weight Per Roll: 42 lb (19 kg)