



**USES:
BASE PLY
BASE SHEET**

PARABASE PLUS

Commercial Product Data Sheet


Parabase Plus is a modified asphalt-coated coated fiberglass sheet used as a base ply or nailable base sheet. Parabase Plus consists of a lightweight random fiberglass mat impregnated and coated with a modified blend of styrene-butadiene-styrene (SBS) and asphalt.

Contact Siplast for information on approved product uses.

PRODUCT INFORMATION

Application

Refer to the applicable Siplast Technical Guide for detailed application information. Parabase Plus is lapped 3 inches (76 mm) side and 6 inches (152.4 mm) end in nailable applications. In approved hot asphalt or adhesive applications, Parabase Plus is lapped 3 inches (76 mm) side and end.



Storage and Handling

All Siplast roll roofing products should be stored on end on a clean, flat surface. Rolls should not be dropped on ends or edges or stored in a leaning position. Deformation resulting from these actions will make proper installation difficult. All roofing products should be stored in a dry place out of direct exposure to the elements and should not be double stacked. Material should be handled so that it remains dry prior to and during installation.

See product packaging and the Safety Data Sheet for specific information on the safe handling of this product.

Packaging

Pallet: 41 in x 48 in (104 cm x 122 cm) wooden pallet
 Rolls Per Pallet: 20
 Pallets Per Truckload: 18
 Minimum Roll Weight: 90 lb (40.8 kg)

Listings, Approvals, & Certifications



Standards	ASTM D4601, Type II
Roll Length	Min: 102.3 ft (31.2 m)
Roll Width	Avg: 3.28 ft (1.0 m)
Coverage	3.0 Squares (27.9 m ²)
Coverage Weight Per Square	Min: 30 lb (1.4 kg/m ²)
Thickness	Avg: 47 mils (1.2 mm) Min: 39 mils (1.0 mm)
Laying Lines	3 in (76 mm) & 13-5/8 in (346 mm) Line Color: Blue
Top Surfacing	Silica Parting Agent
Back Surfacing	Silica Parting Agent

Current copies of all Siplast Commercial Product Data Sheets & Safety Data Sheets are posted on our website at www.siplast.com
 Rev Date 2/2023