



PARABASE PLUS P

Commercial Product Data Sheet

Parabase Plus P is a modified asphalt-coated fiberglass base sheet for nailable applications. Parabase Plus P consists of a lightweight random fiberglass mat impregnated and coated with a modified blend of styrene-butadiene-styrene (SBS) and asphalt. The unique top surface is factory coated with a proprietary Syntan® acrylic coating to facilitate adhesion of self-adhesive base plies.

Contact Siplast for information on approved product uses.


USES: BASE SHEET

PRODUCT INFORMATION

Standards	ASTM D4601 Type II
Roll Length	Min: 102.3 ft (31.2 m)
Roll Width	Avg: 3.28 ft (1.0 m)
Coverage	3.0 Squares (27.9 m ²)
Coverage Weight Per Square	Min: 25 lb (1.1 kg/m ²)
Thickness	Avg: 47 mils (1.2 mm) Min: 39 mils (1.0 mm)
Laying Lines	3 in (76 mm) & 13-5/8 in (346 mm) Line Color: Blue
Top Surfacing	Syntan® Acrylic Coating
Back Surfacing	Silica Parting Agent

Application

Refer to the applicable Siplast Technical Guide for detailed application information and slope limitations. Parabase Plus P is lapped 3 inches (76 mm) side and 6 inches (152.4 mm) end.



Storage and Handling

All Siplast roll roofing products should be stored on end on a clean, flat surface. Rolls should not be dropped on ends or edges or stored in a leaning position. Deformation resulting from these actions will make proper installation difficult. All roofing products should be stored in a dry place out of direct exposure to the elements and should not be double stacked. Material should be handled so that it remains dry prior to and during installation.

See product packaging and the Safety Data Sheet for specific information on the safe handling of this product.

Packaging

Pallet: 41 in x 48 in (104 cm x 122 cm) wooden pallet
Rolls Per Pallet: 20
Pallets Per Truckload: 18
Minimum Roll Weight: 74 lb (33.6 kg)

Listings, Approvals, & Certifications

