

PARABASE PLUS P



Commercial Product Data Sheet

Product Description

Parabase Plus P is a lightly modified asphalt coated fiberglass base sheet or base ply. Parabase Plus P consists of a lightweight random fibrous glass mat impregnated and coated with a modified blend of styrene-butadiene-styrene (SBS) and asphalt. The unique top surface is factory coated with a proprietary Syntan[®] acrylic coating.

Product Uses

Parabase Plus P is designed for use under guaranteed Siplast Roof Systems in certain nailable applications to facilitate adhesion of Paradiene 20 SA. Parabase Plus P is not intended for direct application of Parapro PMMA Liquid Resin. Parabase Plus P is lapped 3 inches (7.6 cm) at sides and 6 inches (15.2 cm) at ends, and is mechanically fastened according to Siplast requirements.

Product Approvals

Parabase Plus P is approved by FM Approvals (FM Standard 4470) for use as a nailed base sheet in Siplast Parapro, Paradiene 20/30, Veral, and Parafor 50 LT non-insulated lightweight concrete roof deck constructions, subject to FM conditions and limitations.

Parabase Plus P has been classified by Underwriters Laboratories as a cUL_{US} rated G2 Base Sheet. Parabase Plus P is approved by Underwriters Laboratories for use in UL Classified Siplast Parapro, Paradiene 20/30, Paradiene 20/30 FR, Veral, Paradiene 40 FR, and Paratech FR Roof Systems. Contact Siplast for specific cUL_{US} Classified roof systems using Parabase Plus P.

Siplast Roof Systems also have received the approval of many regional and local authorities. Please contact Siplast for specific information as required.

COMMERCIAL PRODUCT INFORMATION

Unit:	Roll		
Coverage:	3 Squares	(27.9 m ²)	
Coverage Weight Per Square:	Min:	25 lb	(1.1 kg/m ²)
Roll Length:	Min:	102.3 ft	(31.2 m)
Roll Width:	Avg:	3.28 ft	(1.00 m)
Thickness:	Avg:	47 mils	(1.2 mm)
	Min:	39 mils	(1.0 mm)

Top Surfacing: Syntan Acrylic Coating

Back Surfacing: Silica Parting Agent

Lines: Two laying lines are placed 3 in (7.6 cm) and 13 5/8 in (34.6 cm) from each edge of the material. The line color for this material is blue.

Packaging: The palletted material is protected by a heat shrink polyethylene shroud.

Pallet: 41 in X 48 in (104 cm X 122 cm) wooden pallet
Number Rolls Per Pallet: 20
Number Pallets Per Truckload: 18
Minimum Roll Weight: 74 lb (33.6 kg)

Storage and Handling: All Siplast roll roofing products should be stored on end on a clean flat surface. Care should be taken that rolls are not dropped on ends or edges and are not stored in a leaning position. Deformation resulting from these actions will make proper installation difficult. All roofing should be stored in a dry place, out of direct exposure to the elements, and should not be double stacked. Material should be handled in such a manner as to ensure that it remains dry prior to and during installation.

Current copies of all Siplast Commercial Product Data Sheets are posted on the Siplast Web site at www.Siplast.com.

Rev 2/2018