

PARAFAST® 2.4" BARBED SEAM PLATES

Commercial Product Data Sheet



**USES:
MEMBRANE SEAM PLATE**

Parafast 2.4" Barbed Seam Plates			
Size/Diam.	Product No.	Pieces/Pail	Weight
2.4 in (61 mm)	45S291	1000	50 lb (22.7 kg)

Parafast® 2.4" Barbed Seam Plates (14 barbs) are manufactured from Galvalume® coated steel and are used to attach reinforced singly-ply and modified bituminous membranes to approved substrates using Parafast Fasteners. Parafast 2.4" Barbed Seam Plates are not recommended for securement of rigid insulation panels.

Contact Siplast for more information on approved product uses.

Galvalume® is a registered trademark of BIEC International Inc.

PRODUCT INFORMATION

Application

Refer to the applicable Siplast Technical Guide for detailed application information.

Storage and Handling

All Siplast roofing products should be stored on a clean, flat surface out of direct exposure to the elements. Material should be handled so that it remains dry prior to and during installation.

See product packaging and the Safety Data Sheet for specific information on the safe handling of this product.

Packaging

Packaging: Plastic Pail
 Pails Per Pallet: 24
 Weight Per Pail: 50 lb (22.7 kg)

Listings, Approvals, & Certifications



FM Approved - Refer to RoofNav.com for specific assemblies.