

PARAFAST® 1-STEP LRF CARTRIDGE

Commercial Product Data Sheet



Parafast® 1-Step LRF Cartridge is an elastomeric, all-purpose, foamable adhesive used for adhering rigid insulation boards to substrates approved in advance by Siplast. Designed to be used in one step, Parafast 1-Step LRF Cartridge provides a quick application by eliminating the need for mixing, pump carts, or spray rigs. It has no temperature application restrictions and offers a quick set time.

Contact Siplast for information on approved product uses.

USES: RIGID INSULATION ADHESIVE

Shelf Life*	18 months from Date of Manufacture
Application Coverage Rate**	600 sq ft (56 m ²)
Color	Off White to Light Amber

* Unopened, properly stored product.

**Coverage estimates indicate total square feet of insulation attachment per case. Coverage rates may be lower when used over irregular surfaces and will vary depending on roughness.

PRODUCT INFORMATION

Application

Refer to the Siplast Para-Stik Insulation Adhesive & Parafast Adhesive Installers Guide for detailed application and yield/coverage information.

Storage and Handling

Store Parafast LRF out of direct exposure to the elements at temperatures between 65°F and 85°F (18°C – 29°C). Do not allow Parafast LRF to freeze. Exposure to freezing temperatures may render the product unusable. Material should be handled so that it remains dry prior to and during installation.

See product packaging and the Safety Data Sheet for specific information on the safe handling of this product.

Packaging

50 oz Cartridge (1.5 L)
Cartridges Per Case: 4
Cases Per Pallet: 48

Listings, Approvals, & Certifications



Classified by UL in accordance with ANSI/UL 790. Refer to UL Product iQ for specific assemblies.
FM Approved - Refer to RoofNav.com for specific assemblies.