

PARAFAST® ADHESIVE T CANISTER

Commercial Product Data Sheet



USES:
INSULATION ADHESIVE
ROOF MEMBRANE ADHESIVE

Shelf Life	18 months
Temperature Limitations at Point of Application	Recommended Product Temperature: 70°F (32°C) Ambient & Substrate Temperature Range: 40°F – 100°F (4°C – 38°C)

PRODUCT INFORMATION

Application

Refer to the Siplast Para-Stik Insulation Adhesive & Parafast Adhesive Installers Guide for detailed application and yield/coverage information.

Storage and Handling

All Siplast adhesive products should be stored in a cool, dry location at temperatures between 55°F (13°C) and 85°F (30°C). Care should be taken that containers are not dropped and container seals are not broken prior to use. All roofing products should be stored in a dry place out of direct exposure to the elements and kept away from excessive heat, fire or open flames.

See product packaging and the Safety Data Sheet for specific information on the safe handling of this product.

Packaging

Pallet: 44 in x 48 in (112 cm x 122 cm) wooden pallet
 Weight For Part 1 (Diisocyanate): 48 lb (21.8 kg)
 Weight For Part 2 (Resin): 44 lb (19.6 kg); includes Disposable Hose/Gun Assembly & Related Parts

Units Per Pallet (Parts 1 and/or 2): 32

Listings, Approvals, & Certifications

