



PARAFAST® FASTENER

Commercial Product Data Sheet

The Parafast Fastener is a #12 standard duty roofing screw coated with CR-10 corrosion resistant coating. The Parafast Fastener, in conjunction with the Parafast 3-inch metal plate, is designed to secure roof insulation and substrate panels and base sheets in approved assemblies to standard steel (18-24 gal), wood, and plywood roof decks.

Contact Siplast for information on approved product uses.

USES: ROOFING FASTENER

Head Diameter	0.435 in (11 mm)
Thread Diameter	0.220 in (6 mm)
Head Style	#3 Phillips Truss Head
Drive Bit	#3 Phillips Bit Drive Included in Each Carton

Length	Product No.	Thread Length	Units/ Pkg	Pail Weight
1 5/8 in	45S055	Full	1000	12 lb
2 1/4 in	45S056	Full	1000	16 lb
3 in	45S011	Full	1000	21 lb
4 in	45S012	3 in	1000	26 lb
5 in	45S059	4 in	1000	35 lb
6 in	45S060	4 in	1000	42 lb
7 in	45S061	4 in	1000	48 lb
8 in	45S062	4 in	1000	50 lb

PRODUCT INFORMATION

Application

Refer to the applicable Siplast Technical Guide for detailed application information.



Storage and Handling

All Siplast roofing products should be stored on a clean, flat surface out of direct exposure to the elements. Material should be handled so that it remains dry prior to and during installation.

See product packaging and the Safety Data Sheet for specific information on the safe handling of this product.

Packaging

Primary Packaging: Plastic Pails
 2 gal Pails for Sizes 1 5/8 in – 4 in
 4 gal Pails for Sizes 5 in – 8 in

Pallet: 44 in x 44 in (112 cm x 112 cm) wooden pallet
 Pails Per Pallet: 64 (Sizes 1 5/8 in – 4 in)
 48 (Sizes 5 in – 8 in)
 Pallets Per Truckload: 24

Listings, Approvals, & Certifications

