

PARAFAST® HD #14 DP FASTENER

Commercial Product Data Sheet



The Parafast® HD #14 DP Fastener is a heavy duty roofing screw which is coated with Tru-Kote™ Epoxy E-Coat. The Parafast HD #14 DP Fastener, in conjunction with an appropriate Parafast plate, is designed to secure roof insulation and substrate panels, base sheets, and Parasolo Membranes to structural decks.

Contact Siplast for information on approved product uses.

USES: ROOFING FASTENER

Thread Diameter	0.237 in (2.5 mm)
Shank Diameter	0.180 in (2 mm)
Head Diameter	0.438 in (11 mm)
Head Style	#3 Phillips Truss Head
Drive Bit	#3 Phillips Drive Bit Included

Length	Product No.	Thread Lengths	Units/ Pkg	Pkg Weight
1-1/4 in	45S256	Full	1000	11 lb
1-3/4 in	45S257	Full	1000	16 lb
2 in	45S258	Full	1000	18 lb
3 in	45S259	2-7/8 in	1000	24 lb
4 in	45S260	2-7/8 in	1000	32 lb
5 in	45S261	3-7/8 in	500	21 lb
6 in	45S262	3-7/8 in	500	22 lb
7 in	45S263	3-7/8 in	500	27 lb
8 in	45S264	3-7/8 in	500	31 lb
9 in	45S265	3-7/8 in	500	35 lb
10 in	45S266	3-7/8 in	500	39 lb
11 in	45S2667	3-7/8 in	500	42 lb
12 in	45S268	3-7/8 in	250	24 lb
14 in	45S269	3-7/8 in	250	27 lb

PRODUCT INFORMATION

Application

Refer to the applicable Siplast Technical Guide for detailed application information.



Storage and Handling

All Siplast roofing products should be stored upright on a clean, flat surface out of direct exposure to the elements. Material should be handled so that it remains dry prior to and during installation.

See product packaging and the Safety Data Sheet for specific information on the safe handling of this product.

Packaging

Primary Packaging: Plastic Pails
 Plastic Pails (Various Sizes) for 1 1/4 in - 12 in
 Corrugated Box for 14 in

Listings, Approvals, & Certifications



APPROVED

FM Approved - Refer to RoofNav.com for specific assemblies.