

# PARAFAST® HD FASTENER

## Commercial Product Data Sheet



The Parafast HD Fastener is a #14 heavy duty roofing screw which is coated with CR-10 corrosion resistant coating. The Parafast HD Fastener, in conjunction with appropriate Parafast plate, is designed to secure roof insulation and substrate panels, base sheets, and Parasolo membranes to structural decks.

Contact Siplast for information on approved product uses.

**USES:  
ROOFING FASTENER**

Thread Diameter	0.245 in (2.5 mm)
Shank Diameter	0.190 in (2 mm)
Head Diameter	0.435 in (11 mm)
Head Style	#3 Phillips Truss Head
Drive Bit	#3 Phillips Drive Bit Included in Each Carton

Length	Product No.	Thread Lengths	Units/Pkg	Box Weight
1-1/4 in	45S086	Full	1000	13 lb
1-3/4 in	45S019	Full	1000	17 lb
2 in	45S022	Full	1000	19 lb
3 in	45S023	Full	1000	27 lb
4 in	45S024	3 in	1000	34 lb
5 in	45S025	4 in	500	23 lb
6 in	45S026	4 in	500	26 lb
7 in	45S027	4 in	500	30 lb
8 in	45S028	4 in	500	34 lb
9 in	45S029	4 in	500	37 lb
10 in	45S016	4 in	500	40 lb
11 in	45S017	4 in	500	44 lb
12 in	45S018	4 in	250	25 lb

Longer lengths (up to 24") available upon request. Contact Siplast for information.

### PRODUCT INFORMATION

#### Application

Refer to the applicable Siplast Technical Guide for detailed application information.



#### Storage and Handling

All Siplast roofing products should be stored upright on a clean, flat surface out of direct exposure to the elements. Material should be handled so that it remains dry prior to and during installation.

See product packaging and the Safety Data Sheet for specific information on the safe handling of this product.

#### Packaging

Corrugated Boxes (Various Sizes)

#### Listings, Approvals, & Certifications

