

PARAFAST® INSULATION ADHESIVE C CARTRIDGES

Commercial Product Data Sheet



Parafast Insulation Adhesive C is a fast curing, two-component, bead-applied polyurethane adhesive used to adhere approved rigid insulation panels to substrates approved in advance by Siplast.

Contact Siplast for information on approved product uses.

USES: INSULATION ADHESIVE

Shelf Life	18 months
Temperature Limitations	<p>Recommended Temperature at Point of Application: Minimum 72°F (22°C)</p> <p>Summer Grade Product Ambient & Substrate Temperature: 40°F (5°C) and Rising</p> <p>Winter Grade Product Ambient & Substrate Temperature: 0° (-17°C) and 65°F (19°C)</p>

PRODUCT INFORMATION

Application

Refer to the Siplast Para-Stik Insulation Adhesive & Parafast Adhesive Installers Guide for detailed application and yield/coverage information.

Storage and Handling

All Siplast adhesive products should be stored in a cool, dry location at temperatures between 55°F (13°C) and 85°F (30°C). Do not allow Parafast Insulation Adhesive to freeze under any circumstances. Store materials out of direct exposure to the elements. All material stored on the roof overnight should be stored on pallets. When storing materials on the roof, do not overload the deck or structural assembly.

See product packaging and the Safety Data Sheet for specific information on the safe handling of this product.

Packaging

Gross Weight: 19 lb (8.6 kg); including 4-1500 mL cartridges & packaging
Cases Per Pallet: 40

Listings, Approvals, & Certifications

