



## PARAFAST® LD FASTENER

### Commercial Product Data Sheet

The Parafast LD Fastener is a specialty roofing screw coated with CR-10 corrosion resistant coating. The Parafast LD Fastener, in conjunction with Parafast LD plates, is designed to secure roof insulation, substrate panels, and base sheets in approved assemblies to cementitious-wood fiber and gypsum roof decks.

Contact Siplast for information on approved product uses.

#### USES: ROOFING FASTENER

Thread Diameter	0.375 in (9.5 mm)
Shank Diameter	0.312 in (8 mm)
Head Diameter	0.710 in (18 mm)
Head Style	6-Lobe (T-40) Drive Flat Head
Drill Bit	A Bit is Included in Each Carton

Length	Product No.	Thread Lengths	Units/ Pkg	Box Weight
2 5/8 in	45S103	2 5/8 in	500	32 lb
3 in	LDF300	3 in	500	36 lb
4 in	LDF400	3 in	500	47 lb
5 in	LDF500	3 in	250	30 lb
6 in	LDF600	3 in	250	36 lb
7 in	LDF700	3 in	250	41 lb
8 in	45S117	3 in	250	46 lb
9 in	45S139	3 in	125	26 lb
10 in	45S140	3 in	125	29 lb
12 in	45S141	3 in	125	34 lb

## PRODUCT INFORMATION

### Application

Refer to the applicable Siplast Technical Guide for detailed application information.



### Storage and Handling

All Siplast roofing products should be stored upright on a clean, flat surface out of direct exposure to the elements. Material should be handled so that it remains dry prior to and during installation.

See product packaging and the Safety Data Sheet for specific information on the safe handling of this product.

### Packaging

Primary Packaging: Corrugated Boxes  
 Pallet: 44 in x 44 in (112 cm x 112 cm) wooden pallet  
 Boxes Per Pallet: 80  
 Pallets Per Truckload: 24

### Listings, Approvals, & Certifications

