

# PARAFAST® PG-1 LRF CARTRIDGES, 5-GAL, & 15 GAL

## Commercial Product Data Sheet



Parafast® PG-1 LRF is a fast-curing, two-component, low-rise foam adhesive used to adhere approved rigid insulation panels to substrates approved in advance by Siplast.

Contact Siplast for information on approved product uses.

### USES: RIGID INSULATION ADHESIVE

Shelf Life*	18 months from Date of Manufacture
Recommended Product Temp. at Time of Application	Min. 70°F (20°C)
Ambient & Substrate Temp. Range at Time of Application	25°F (-4°C) and rising
50 oz Cartridge Coverage Rate**	600 sq ft (56 m <sup>2</sup> )
5-Gallon Bag-in-Box Kit Coverage Rate**	2,500 – 3,000 sq ft (232-279 m <sup>2</sup> )
15-Gallon Drum Kit Coverage Rate**	7,500 – 9,000 sq ft (697-836 m <sup>2</sup> )

\* Unopened, properly stored product.

\*\*Coverage estimates indicate total square feet of insulation attachment per case of four (4) 50 oz cartridges. Coverage rates may be lower when used over irregular surfaces and will vary depending on roughness.

### PRODUCT INFORMATION

#### Application

Refer to the Siplast Para-Stik Insulation Adhesive & Parafast Adhesive Installers Guide for detailed application and yield/coverage information.

#### Storage and Handling

Store Parafast LRF out of direct exposure to the elements at temperatures between 45°F and 95°F (7°C – 35°C). Do not allow Parafast LRF to freeze. Exposure to freezing temperatures may render the product unusable. Material should be handled so that it remains dry prior to and during installation.

See product packaging and the Safety Data Sheet for specific information on the safe handling of this product.

#### Packaging

50 oz Cartridge (1.5 L), 4 Cartridges Per Case  
Cases per Pallet: 48

5-gal Bag-in-Box (10 gal per A & B set)  
Weight for Part A: 52 lb (23.6 kg); including packaging  
Weight for Part B: 43 lb (19.5 kg); including packaging  
Units Per Pallet (A or B): 36 (18 sets)

15-gal Plastic Drums (30 gal per A & B set)  
Weight for Part A: 162 lb (73.5 kg); including drum  
Weight for Part B: 136 lb (61.7 kg); including drum  
Units Per Pallet (A or B): 8 (4 sets)

#### Listings, Approvals, & Certifications



Classified by UL in accordance with ANSI/UL 790. Refer to UL Product iQ for specific assemblies.  
FM Approved - Refer to RoofNav.com for specific assemblies.

Current copies of all Siplast Commercial Product Data Sheets & Safety Data Sheets are posted on our website at [www.siplast.com](http://www.siplast.com)

Rev Date 6/2023