

# PARAFAST® RHINOBOND® TPO PLATES

Commercial Product Data Sheet

Parafast<sup>®</sup> RhinoBond<sup>®</sup> TPO Plates are manufactured from Galvalume<sup>®</sup> coated steel and coated with TPO to allow for induction welding of Parasolo TPX membranes to the installed plate.

Contact Siplast for information on approved product uses.

#### USES: PARASOLO TPX ACCESSORY

Parafast RhinoBond TPO XHD Plates				
Size / Diam.	Product No.	Units/Pail	Weight	
3 in (80 mm)	45S216	500	43 lb	

Parafast RhinoBond TPO SXHD Plates				
Size / Diam.	Product No.	Units/Pail	Weight	
3 in (80 mm)	Pending	500	43 lb	

# **PRODUCT INFORMATION**

### Application

Refer to the applicable Siplast Technical Guide for detailed application information.

### Storage and Handling

All Siplast roofing products should be stored upright on a clean, flat surface out of direct exposure to the elements. Material should be handled so that it remains dry prior to and during installation.

See product packaging and the Safety Data Sheet for specific information on the safe handling of this product.

### Packaging

Primary Packaging: Plastic Pail Pails Per Pallet: 40

## Listings, Approvals, & Certifications



FM Approved: Refer to RoofNav.com for specific assemblies.

RhinoBond<sup>®</sup> is a registered trademark of OMG, Inc. Galvalume<sup>®</sup> is a registered trademark of BIEC International, Inc.

Current copies of all Siplast Commercial Product Data Sheets & Safety Data Sheets are posted on our website at www.siplast.com Rev Date 5/2023