

PARAFAST® SXHD FASTENER

Commercial Product Data Sheet



Parafast SXHD Fasteners are a #21 special purpose screw coated with CR-10 corrosion resistant coating. The Parafast SXHD Fastener, in conjunction with appropriate metal plates, are designed to secure roof insulation/substrate panels, base sheets and Parasolo Membranes in approved assemblies to steel roof decks and other substrates that are approved in advance by Siplast.

Contact Siplast for information on approved product uses.

**USES:
ROOFING FASTENER**

Head Diameter	0.500 in (12.7 mm)
Thread Diameter	0.325 in (9.53 mm)
Head Style	#3 Phillips Truss Head

Length	Product No.	Thread Length	Units/ Pkg	Box Weight
2 in	45S138	1.75 in	500	11 lb
3 in	45S137	2.75 in	500	22 lb
4 in	45S124	3 in	500	29 lb
5 in	45S135	3 in	500	36 lb
6 in	45S091	4 in	500	44 lb
7 in	45S092	4 in	250	26 lb
8 in	45S123	4 in	250	29 lb
9 in	45S162	4 in	250	32 lb
10 in	45S163	4 in	250	35 lb
12 in	45S164	4 in	250	42 lb

PRODUCT INFORMATION

Application

Refer to the applicable Siplast Technical Guide for detailed application information.

Storage and Handling

All Siplast roofing products should be stored upright on a clean, flat surface out of direct exposure to the elements. Material should be handled so that it remains dry prior to and during installation.

See product packaging and the Safety Data Sheet for specific information on the safe handling of this product.

Packaging

Plastic Pails (Various Sizes)