

# PARAFAST® TERM BAR

## Commercial Product Data Sheet



Parafast Term Bar is designed to terminate single-ply membranes at parapet walls, curbs, and other penetrations. Parafast Term Bar is available in both flat and lip variants.

Contact Siplast for information on approved product uses.

**USES:  
PARASOLO ACCESSORY**

<b>Composition</b>	Extruded Aluminum (6063 T6 Alloy)
<b>Thickness</b>	90 mils (2.3 mm)
<b>Width/Length</b>	1 in (25 mm) 10 ft (3.05 m)
<b>Lip</b>	3/16 in (5 mm) at 45°F (7°C) (Lip-Bar only)
<b>Hole Size/Spacing</b>	1/4 in (6 mm) x 3/8 in (10 mm) 6 in (150 mm) o.c.

### PRODUCT INFORMATION

#### Application

Refer to the applicable Siplast Parasolo Technical Guide and Details for information on installation of Parafast Term Bar.

#### Storage and Handling

All roofing products should be stored in a dry place out of direct exposure to the elements. Material should be handled so that it remains dry prior to and during installation.

See product packaging and the Safety Data Sheet for specific information on the safe handling of this product.

#### Packaging

Packaging: 50 pieces (500 linear feet) (152.2 linear meters) in corrugated tube  
Weight: 57 lb (25.88 kg) per tube