

PARAFAST® XHD FASTENER (#15)

Commercial Product Data Sheet



**USES:
ROOFING FASTENER**

| | |
|-----------------|------------------------|
| Head Diameter | 0.435 in (11.04 mm) |
| Shank Diameter | 0.202 in (5.13 mm) |
| Thread Diameter | 0.265 in (6.73 mm) |
| Head Style | #3 Phillips Truss Head |

| Length | Item No. | Thread Length | Units/ Pkg | Box Weight |
|--------|----------|---------------|---------------|------------|
| 2 in | 86SPA | full | 1000 | 20 lb |
| 3 in | 86SPB | full | 1000 | 29lb |
| 4 in | 86SPC | 3 in | 1000 | 38 lb |
| 5 in | 86SPD | 4 in | 500 | 24 lb |
| 6 in | 86SPE | 4 in | 500 | 28 lb |
| 7 in | 86SPF | 4 in | 500 | 34 lb |
| 8 in | 86SPG | 4 in | 500 | 38 lb |
| 9 in | 86SPH | 4 in | 500 | 43 lb |
| 10 in | 86SPI | 4 in | 500 | 47 lb |
| 11 in | 86SPJ | 4 in | 500 | 51 lb |
| 12 in | 86SPK | 4 in | 500 | 56 lb |

Other lengths available (up to 24").

PRODUCT INFORMATION

Application

Refer to the applicable Siplast Technical Guide for detailed application information.

Storage and Handling

All Siplast roofing products should be stored upright on a clean, flat surface out of direct exposure to the elements. Material should be handled so that it remains dry prior to and during installation.

See product packaging and the Safety Data Sheet for specific information on the safe handling of this product.

Packaging

Plastic Pails (up to 12")
Longer lengths packaged in boxes.

Listings, Approvals, & Certifications



FM Approved - Refer to RoofNav.com for specific assemblies.