



# PARAFAST® XHD FASTENER

## Commercial Product Data Sheet

Parafast XHD Fasteners are a #15 special purpose screws with a CR-10 corrosion resistant coating. The Parafast XHD Fastener, in conjunction with appropriate metal plates, are designed to secure roof insulation/substrate panels, base sheets, and Parasolo Membranes in approved assemblies to steel roof decks and other substrates that are approved in advance by Siplast.

Contact Siplast for information on approved product uses.

**USES:  
ROOFING FASTENER**

Head Diameter	0.435 in (11.04 mm)
Shank Diameter	0.202 in (5.13 mm)
Thread Diameter	0.265 in (6.73 mm)
Head Style	#3 Phillips Truss Head

Length	Item No.	Thread Length	Units/ Pkg	Box Weight
2 in	XHDF200	full	1000	20 lb
3 in	XHDF300	full	1000	29lb
4 in	XHDF400	3 in	1000	38 lb
5 in	XHDF500	4 in	500	24 lb
6 in	XHDF600	4 in	500	28 lb
7 in	XHDF700	4 in	250	34 lb
8 in	HXD800	4 in	250	38 lb
9 in	XHD900	4 in	250	42 lb
10 in	XHDF1000	4 in	250	47 lb
12 in	XHDF1200	4 in	250	52 lb

Other lengths available (up to 24").

### PRODUCT INFORMATION

#### Application

Refer to the applicable Siplast Technical Guide for detailed application information.

#### Storage and Handling

All Siplast roofing products should be stored upright on a clean, flat surface out of direct exposure to the elements. Material should be handled so that it remains dry prior to and during installation.

See product packaging and the Safety Data Sheet for specific information on the safe handling of this product.

#### Packaging

Plastic Pails (up to 12")  
Longer lengths packaged in boxes.

#### Listings, Approvals, & Certifications

