



PARASOLO™ ONE-PART POURABLE SEALANT

Commercial Product Data Sheet

Parasolo One-Part Pourable Sealant is a one-part, moisture-cure, self-leveling sealant for use in Parasolo Pourable Sealant Pockets. Parasolo 1-Part Pourable Sealant is used to seal irregular penetrations that cannot be flashed using conventional boot flashings or liquid-applied flashings.

Contact Siplast for information on approved product uses.

USES: PARASOLO ACCESSORY

Color	White
Density	8.9 lb. (± 0.2 lb.) per gallon (1.07 g/ml)
Elongation	300% (± 25%)
Tensile Strength	146 lbf (217 kg/m)
VOC	< 25 g/L
Service Temperature	-40°F – 200°F (-40°C – 93.3°C)

PRODUCT INFORMATION

Application

Refer to the applicable Siplast Technical Guide for detailed information on the application of Parasolo membrane accessories. Surfaces should be clean, dry, and free of any loose materials. Remove all previously applied caulk, mastic, cement and any other contaminants that could affect adhesion. Do not apply at temperatures below 30°F (-1°C) or if rain is anticipated within 4 hours. Clean-up with alcohol or non-petroleum solvents before the sealer cures.

Storage and Handling

Store unopened containers in a cool, dry area between 40°F – 90°F (4°C – 32.2°C). Protect unopened containers from water, heat, and direct sunlight. Store indoors before use to ensure easy application and leveling. Shelf life is one year from date of manufacture when stored under the conditions outlined above. Exposure to elevated temperatures and/or relative humidity may significantly reduce shelf life.

See product packaging and the Safety Data Sheet for specific information on the safe handling of this product.

Packaging

Primary Packaging: 0.53 gal (2 L) pouch
 Pouches Per Case: 4
 Cases Per Pallet: 48