

# PARASOLO™ PVC MEMBRANE CONDITIONER

## Commercial Product Data Sheet



Parasolo PVC Membrane Conditioner is a solvent used to clean exposed, contaminated or aged PVC membrane surfaces prior to heat welding.

Contact Siplast for information on approved product uses.

### USES: PARASOLO PVC ACCESSORY

Color	Clear Liquid
Container Size	1 gallon F-Style Can (3.78 L)
Density @ 25°C	6.55 lb. per gallon (0.7844 g/mL)
Flash Point	-4°F (-20°C) Closed Cup

### PRODUCT INFORMATION

#### Application

Refer to the applicable Siplast Technical Guide for detailed information on the use of Parasolo PVC Membrane Conditioner. Note that embedded dirt or contamination may require the use of an abrasive scrubbing pad and a low-residue cleaning solution such as Formula 409® prior to cleaning with Parasolo PVC Membrane Conditioner.

#### Storage and Handling

Keep container closed when not in use. Store unopened containers in a cool, dry and well-ventilated place away from heat and all ignition sources. See product packaging and the Safety Data Sheet (SDS) for specific information on the safe handling of this product.

See product packaging and the Safety Data Sheet for specific information on the safe handling of this product.

#### Packaging

Primary Packaging: F-Style Metal Can  
Weight Per Can: 8 lbs (0.363 kg)  
DOT Classification: 1090, Class: 3, Flammable Liquid