

PARASOLO® PVC QUICK-LAY ADHESIVE

Commercial Product Data Sheet



USES:
MEMBRANE ADHESIVE
FLASHING ADHESIVE

Color	White
Solids Content	65.5% (± 1.5%)
VOC	< 50 g/L
Weight	8.5 lb/gal (1 kg/L)
Viscosity	10,000 cps
Shelf Life	1 year (unopened)
*Coverage	50-70 ft ² /gal (1.2-1.7 m ² /L) 250-350 ft ² /pail (23.2-27.8 m ² /pail)

*Substrate porosity and ambient conditions may affect coverage rates.

Parosolo PVC Quick-Lay Adhesive is a water-based bonding adhesive specifically designed for bonding Parosolo PVC single-ply roofing membranes and flashings to approved substrates. Note that Parosolo PVC Quick-Lay Adhesive is approved for use only with Parosolo PVC and not Parosolo PVC KEE membranes.

Contact Siplast for information on approved product uses.

PRODUCT INFORMATION

Application

Refer to the applicable Siplast Installers Guide for detailed information on application of Parosolo membranes in Parosolo PVC Quick-Lay Adhesive. **Note that Parosolo PVC Quick-Lay Adhesive is not approved for use with Parosolo PVC KEE membranes.**



Storage and Handling

Store material in a clean and well-ventilated area above 40°F (4.4°C). Do not allow product to freeze as it will be rendered unusable. Keep containers covered when not in use. See product packaging for Hazard and Precautionary information.

See product packaging and the Safety Data Sheet for specific information on the safe handling of this product.

Packaging

Primary Packaging: 5 gal (18.93 L) plastic pails
Weight: 44 lb (19.96 kg)

Listings, Approvals, & Certifications

