

PARASOLO® PVC QUICK SPRAY ADHESIVE

Commercial Product Data Sheet



Parasolo® PVC Quick Spray Adhesive is a single-component adhesive dispensed from a pressured metal canister and is used to adhere smooth Parasolo PVC and Parasolo PVC KEE membranes to substrates approved in advance by Siplast.

Contact Siplast for information on approved product uses.

USES:
PVC MEMBRANE ADHESIVE

Shelf Life	12 months
Application Temperature Limitations	<p>Minimum Ambient & Substrate Temperature at Point of Application: 20°F (-7°C)(PVC Membranes) 40°F (4.4°C)(PVC KEE Membranes)</p> <p>Minimum Product Temperature at the Time & Point of Application: 70°F (21°C)*</p>
Typical Application Rate	Up to 7.5 sq (69.7 m ²) per Canister**
VOC	< 250 g/L

* Product will not dispense properly if maintained/used at temperatures lower than the above.

**Coverage rates and flash time may vary at the lower end of ambient/substrate temperature conditions.

PRODUCT INFORMATION

Application

Refer to the applicable Siplast Technical Guide for detailed application information. Product can be dispensed using hose/gun kits approved for this product and equipment can be cleaned using an approved hose and nozzle cleaner.

Storage and Handling

Store Parasolo PVC Quick Spray Adhesive out of direct exposure to the elements and in a cool, dry location at temperatures between 45°F (7°C) and 90°F (32.2°C). Do not allow the product to reach a temperature of 150°F (65.5°C) under any circumstances. All material stored on the roof overnight should be stored on pallets. When storing materials on the roof, do not overload the deck or structural assembly.

Packaging

Weight of Full Canister Unit (including packaging): 40.15 lb (18.1 kg)
Tanks Per Pallet: 24

Listings, Approvals, & Certifications

