

# PARASOLO® TPX SPLIT PIPE BOOT

# Commercial Product Data Sheet



Parasolo® TPX Split Pipe Boots are fabricated from reinforced Parasolo TPX Membrane and are used for flashing round and conical penetrations. Split boots can be used to flash penetrations that cannot be overlaid with a closed boot.

Contact Siplast for information on approved product uses.

#### USES: FLASHING PARASOLO TPX ACCESSORY

Color	White
Thickness	45 mils (1.14 mm)
	1" - 2" (25.4 mm - 50.8 mm)
For Pipe Diameters	3" – 5" (76.2 mm – 127 mm)
	6" - 8" (152.2 mm - 203.2 mm)

# PRODUCT INFORMATION

### Application

Refer to the applicable Siplast Technical Guide and applicable Siplast details for information on the application of Parasolo TPX Split Pipe Boots.



## Storage and Handling

All Siplast roofing products should be stored on a clean, flat surface. All roofing products should be stored in a dry place out of direct exposure to the elements. Material should be handled so that it remains dry prior to and during installation.

See product packaging and the Safety Data Sheet for specific information on the safe handling of this product.

### **Packaging**

Units Per Box: 6

Weight Per Box: 1" - 2" Boots: 7.5 lb (3.4 kg)

3" - 5" Boots: 7.5 lb (3.4 kg) 6" - 8" Boots: 11 lb (5 kg)

Boxes Per Pallet: 1" - 2" Boots: 36

3" - 5" Boots: 36 6" - 8" Boots: 24