

PARASOLO® TPX SPLIT POURABLE SEALER POCKET

Commercial Product Data Sheet

Parasolo[®] TPX Split Pourable Sealer Pocket is fabricated from a proprietary formula that is compatible with Parasolo TPX Membrane and is used for flashing around irregular penetrations. The split pourable sealer pocket should be used with Parasolo One-Part Pourable Sealant.

Contact Siplast for information on approved product uses.

USES: FLASHING PARASOLO TPX ACCESSORY

Color	White
Thickness	65 mils (1.7 mm)
Pocket Width	Outside – 19 in (383 mm) Inside – 7 in (178 mm)
Pocket Length	Outside – 25 in (635 mm)* Inside – 13 in (330 mm)**
Height of Pocket Wall	2 in (51 mm)

*Can be cut to 19 in (483 mm) **Can be cut to 7 in (178 mm)

PRODUCT INFORMATION

Application

Refer to the applicable Siplast Technical Guide and applicable Siplast details for information on the application of Parasolo TPX Split Pourable Sealer Pocket.



Storage and Handling

All Siplast roofing products should be stored on a clean, flat surface. All roofing products should be stored in a dry place out of direct exposure to the elements. Material should be handled so that it remains dry prior to and during installation.

See product packaging and the Safety Data Sheet for specific information on the safe handling of this product.

Packaging

Units Per Box: 6 complete pockets Weight Per Box: 6 lb (2.72 kg) Boxes Per Pallet: 12 Pallet Size: 48 in (1,219 mm) x 48 in (1,219 mm)

Current copies of all Siplast Commercial Product Data Sheets & Safety Data Sheets are posted on our website at www.siplast.com Rev Date 03/2024