



USES:
PARASOLO ACCESSORY

PARASOLO™ WATERBLOCK SEALANT

Commercial Product Data Sheet

Parasolo Waterblock Sealant is a black, butyl-based high-viscosity sealant for use in conjunction with Siplast Parasolo series single-ply membrane systems. Parasolo Waterblock Sealant is designed for use in concealed applications such as sealing between Parasolo membranes and drain/penetration flashings.

Contact Siplast for information on approved product uses.

PRODUCT INFORMATION

Total Solids by Weight	>85%
Specific Gravity	1.24 ± 0.1
Application Temp. (Ambient & Substrate)	32°F – 120°F (0°C – 48.9°C)
Shelf Life	12 months (if unopened)

Application

Refer to the applicable Siplast Technical Guide for detailed information on application of Parasolo and Parasolo KEE membrane accessories. Clean-up with mineral spirits, toluene or xylene.

Do not use Parasolo Waterblock Sealant in conjunction with Siplast SBS Membrane Systems. Parasolo Waterblock Sealant is not approved for applications in which the product will be exposed to UV.



Storage and Handling

Store material in a clean and well-ventilated area at 50°F (10°C) – 90°F (32.2°C). Storage for extended periods outside this temperature range may shorten shelf life. Do not apply at temperatures of less than 32°F (0°C) or above 120°F (48.9°C).

See product packaging and the Safety Data Sheet for specific information on the safe handling of this product.

Packaging

Primary Packaging: 10-oz cartridge
 Tubes Per Box: 25
 Weight Per Box: 13 lb (5.9 kg)