

PARASOLO® WB BONDING ADHESIVE

Commercial Product Data Sheet



Parasolo® WB Bonding Adhesive is a water-based, copolymer-based acrylic emulsion adhesive used in bonding both TPO smooth and fleece-back and PVC fleece-back roofing membranes to various substrates.

Contact Siplast for information on approved product uses.

USES:
TPO/PVC MEMBRANE ADHESIVE
TPO/PVC FLASHING ADHESIVE

PRODUCT INFORMATION

Application

Refer to the applicable Siplast Technical Guide and applicable Siplast details for information on the application of Parasolo TPX and PVC membranes with Parasolo WB Bonding Adhesive.



Storage and Handling


Store material in a clean and well-ventilated area above 40°F – 90°F (4.4°C – 32.2°C). Storage for extended periods outside this temperature range may shorten shelf life. Keep containers covered when not in use. **Do not** allow adhesive to freeze.

See product packaging and the Safety Data Sheet for specific information on the safe handling of this product.

Packaging

Primary Packaging: 5-gal (18.93 L) metal pails
 Pails Per Pallet: 45
 Weight: 45 lb (20.4 kg)

Listings, Approvals, & Certifications



Classified by UL in accordance with ANSI/UL 790. Refer to UL Product iQ for specific assemblies.
 FM Approved: Refer to RoofNav.com for specific assemblies.

Color	Off White
Weight Per Gallon	8.6 – 9.0 lb (3.9 – 4.1 kg/L)
Viscosity	14,000 – 18,000 cps (Brookfield)
Coverage (Approximately)	Smooth Reinforced Membrane: 1 gal Per 115 – 125 sq ft Fleece-Back Membrane: 1 gal Per 100 – 200 sq ft
Solids Content	60.0 – 65.0%
VOC	<20 g/L
Minimum Application Temperature	40°F (4.4°C) and Rising