



PARATREAD®

Commercial Product Data Sheet

Paratread is an SBS modified bitumen sheet material designed to be used as a walktread in roof areas with anticipated high pedestrian traffic or mechanical abuse potential. Paratread is composed of an asphalt impregnated, puncture resistant polyester fabric core, coated with a polymer modified bitumen and topped with a ceramic-coated granule wearing surface.

Contact Siplast for information on approved product uses.

USES: WALKTREAD

Coverage	50 ft ² (4.7 m ²)
Weight per Square Foot	1.4 lb (6.8 kg/mg ²)
Roll Length	20 ft (6.10 m)
Roll Width	30 in (76 cm)
Roll Weight	72 lb (32.6 kg)
Thickness	217 mils (5.5 mm)
Top Surfacing	#11 Roofing Granules Stone Gray #701
Bottom Surfacing	Perforated Plastic Film

PRODUCT INFORMATION

Application

Refer to the applicable Siplast Technical Guide and details for detailed application information.

Storage and Handling

All Siplast roll roofing products should be stored on end on a clean, flat surface. Care should be taken that rolls are not dropped on ends or edges and are not stored in a leaning position. Deformation resulting from these actions will make proper installation difficult. All materials should be stored in a dry place, out of direct exposure to the elements, and should be handled in such a manner as to ensure that the materials remain dry prior to and during installation.

See product packaging and the Safety Data Sheet for specific information on the safe handling of this product.

Packaging

Pallet: 39 in x 39 in (99 cm x 99 cm) wooden pallet
 Rolls Per Pallet: 20
 Pallets Per Truckload: 40