



# PRO GRID REINFORCEMENT

## Commercial Product Data Sheet

Pro Grid Reinforcement is a fiberglass scrim reinforcement designed for use in Terapro and Terapro VTS Systems. Pro Grid Reinforcement is embedded in Pro Primer and is followed by Terapro and Terapro VTS Wearing/Surfacing Components.

Contact Siplast for specific information on approved product uses.

**USES:  
REINFORCEMENT FOR  
LIQUID-APPLIED SYSTEMS**

Roll Size	150 linear yds @ 47 in width (450 ft x 3.91 ft)
Roll Weight	Approx. 100 lbs (45.36 kg)
Coverage per Roll	1,762 ft <sup>2</sup> (163.6 m <sup>2</sup> )

### PRODUCT INFORMATION

#### Application

Refer to the applicable Siplast Technical Guide and related supplements for detailed application information.

#### Storage and Handling

All Siplast roofing and waterproofing products should be stored on a clean and dry surface away from direct exposure to the elements, excessive heat, sunlight and open flames. Store in a manner that will prevent deformation of rolls or creasing of the grid. Pro Grid Reinforcement has a shelf life of 12 months from the date of manufacture. Exposure to sunlight and/or temperatures exceeding 100°F (38°C) may affect shelf life.

See product packaging and the Safety Data Sheet for specific information on the safe handling of this product.

#### Packaging

Rolls Per Pallet: 16