

# RT SURFACE TREATMENT

## Commercial Product Data Sheet



RT Surface Treatment is a blend of bitumen and polymeric binder in the form of a black pellet coated with a release agent. RT Surface Treatment is a bond-enhancing component for use in semi-adhering Paradiene 20 TS Systems directly to the surface of Insulcel Lightweight Insulating Concrete.

Contact Siplast for information on approved product uses.

### USES: SLIC SURFACE TREATMENT

Color	Dark Brown to Black
Bulk Density	40 lb/ft <sup>3</sup> (640.7 kg/m <sup>3</sup> )
Pellet Size	Diameter: 3 – 5 mm (0.12 – 0.20 in)

### PRODUCT INFORMATION

#### Application

Refer to the applicable Siplast Technical Guide for detailed application information.



#### Storage and Handling

All Siplast roofing products should be stored in a dry location out of direct exposure to the elements and should not be double stacked. RT Surface Treatment pellets are an asphalt-based material and must be stored under conditions that do not cause consolidation of the pellets.

See product packaging and the Safety Data Sheet for specific information on the safe handling of this product.

#### Packaging

Plastic Bags: 55 lb (20 kg)  
Bags Per Pallet: 25  
Weight Per Pallet: 1,375 lb (624 kg)