

SFT[®] ADHESIVE

Commercial Product Data Sheet

SFT Adhesive is a 100% solids, low-odor liquid adhesive designed for use with Siplast Paradiene 20/30, Paradiene 40 FR, Parafor 50 LT Roofing Systems, and Teranap Waterproofing Systems. SFT Adhesive is a single-component blend of proprietary polymers, and asphalt.

Contact Siplast for information on approved product uses.


USES: ROOF MEMBRANE ADHESIVE

Typical Coverage	Base Ply: 1.5 – 2.5 gal/sq (0.6-1.0 L/m ²) Interply: 1.5 – 2 gal/sq (0.6-0.8 L/m ²)
Thickness	1.5 gal/sq: 24 mils (0.6 mm) 2.5 gal/sq: 40 mils (1.0 mm)
Coverage Weight	1.5 gal/sq: 15 lb/sq (0.7 kg/m ²) 2.5 gal/sq: 25 lb/sq (1.2 kg/m ²)
VOC Content	< 32 g/L ASTM D2369, EPA Method 24
Recommended Adhesive Temp. at Point of Application	Minimum 70°F (21°C)
Shelf Life	6 months (When stored at 70°F (21°C) at 50% RH)

PRODUCT INFORMATION

Application

Refer to the applicable Siplast Technical Guide for detailed application information.



Storage and Handling

All Siplast adhesive products should be stored on a clean, flat surface. Care should be taken that containers are not dropped and container seals are not broken prior to use. All roofing products should be stored in a dry, cool place out of direct exposure to the elements and kept away from excessive heat, fire, or open flames. Storage under high-temperature/humidity conditions will significantly reduce the shelf life.

See product packaging and the Safety Data Sheet for specific information on the safe handling of this product.

Packaging

Pallet: 44 in x 48 in (112 cm x 122 cm) wooden pallet
Pails Per Pallet: 36
Pallets Per Truckload: 22
Weight Per Pail: 53 lb (24 kg)
Weight Per Pallet: 1960 lb (889 kg)

Listings, Approvals, & Certifications

