

SFT® CEMENT

Commercial Product Data Sheet



SFT Cement is a 100% solids, low-odor flashing adhesive designed for use with Veral Aluminum, Paradiene 40 FR, and Parafor flashing sheets. SFT® Cement is single-component, blend of proprietary polymers and modifiers and is intended specifically for use as a flashing cement, but may also be used as a multi-purpose adhesive in approved applications.

Contact Siplast for information on approved product uses.

USES:
FLASHING MEMBRANE ADHESIVE

Typical Coverage	<p>Base Ply: 2 – 2.5 gal/sq (0.8-1.0 L/m²)</p> <p>Interply: 2 – 3 gal/sq (0.8-1.2 L/m²)</p>
Thickness	<p>2 gal/sq: 32 mils (0.8 mm)</p> <p>3 gal/sq: 48 mils (1.2 mm)</p>
Coverage Weight	<p>2 gal/sq: 26 lb/sq (1.3 kg/m²)</p> <p>3 gal/sq: 39 lb/sq (1.9 kg/m²)</p>
VOC Content	<p>< 11 g/L</p> <p>ASTM D2369, EPA Method 24</p>
Recommended Adhesive Temp. at Point of Application	<p>Minimum 70°F (21°C)</p>

PRODUCT INFORMATION

Application

Refer to the applicable Siplast Technical Guide for detailed application information.

Storage and Handling

All Siplast adhesive roofing products should be stored on a clean, flat surface. Care should be taken that containers are not dropped and container seals are not broken prior to use. All roofing products should be stored in a dry place out of direct exposure to the elements and kept away from excessive heat, fire, or open flames. Storage under high-temperature/humidity conditions will significantly reduce the shelf life.

See product packaging and the Safety Data Sheet for specific information on the safe handling of this product.

Packaging

Pallet: 44 in x 48 in (112 cm x 122 cm) wooden pallet
 Pails Per Pallet: 60
 Pallets Per Truckload: 36
 Weight Per Pail: 27 lb (12.2 kg)
 Weight Per Pallet: 1660 lb (753 kg)