

# ZONO-TITE® FASTENER

## Commercial Product Data Sheet



The Zono-Tite Fastener is formed from specially coated galvanized steel. The split wedge leg spreads upon installation into lightweight insulating concrete to provide withdrawal resistance. Zono-Tite Fasteners are assembled to incorporate a corrosion resistant Galvalume-coated stress distribution plate.

Contact Siplast for information on approved product uses.

### USES: BASE SHEET FASTENER

Color	Black Fastener with Attached Silver/Gray Plate
Unit Length	Nominal 1.7 in (4.3 cm)
Plate Diameter	2.7 in (6.9 cm)
Quantity per Box	1,000

### PRODUCT INFORMATION

#### Application

Refer to the applicable Siplast Technical Guide for detailed application information.

#### Storage and Handling

All Siplast roofing products should be stored upright on a clean, flat surface out of direct exposure to the elements. Material should be handled so that it remains dry prior to and during installation.

See product packaging and the Safety Data Sheet for specific information on the safe handling of this product.

#### Packaging

Primary Packaging: Corrugated Boxes  
 Box Size: 14 in x 14 in x 23 in (35 cm x 35 cm x 58 cm)  
 Pallet: 44 in x 44 in (112 cm x 112 cm)  
 Boxes Per Pallet: 18  
 Weight Per Box: 35 lb (15.8 kg)

Fastener Head Stamp: Z-T

#### Listings, Approvals, & Certifications

