



1. Identification

| | |
|---|--|
| Product identifier | PA-1125 Primer |
| Other means of identification | Not available. |
| Recommended use | Primer. |
| Recommended restrictions | None known. |
| Manufacturer/Importer/Supplier/Distributor information | |
| Supplier | |
| Supplier | Siplast, Inc. |
| Division | Asphalt Roofing |
| Address | 1111 Highway 67 S Arkadelphia, AR 71923 |
| Website | www.siplast.com |
| E-Mail | ussds@siplast.com |
| Hours of Operation | 08:00 AM - 05:00 PM (US Central Standard Time) |
| Siplasr General Assistance | 1.800.922.8800 |
| CHEMTREC | 1.800.424.9300 |

2. Hazard(s) identification

| | | |
|------------------------------|-------------------|------------|
| Physical hazards | Flammable liquids | Category 3 |
| Health hazards | Not classified. | |
| Environmental hazards | Not classified. | |
| OSHA defined hazards | Not classified. | |

Label elements



| | |
|--|--|
| Signal word | Warning |
| Hazard statement | Flammable liquid and vapor. |
| Prevention | Use only non-sparking tools. Use explosion-proof electrical/ventilating/lighting equipment. Ground/bond container and receiving equipment. Take precautionary measures against static discharge. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. No smoking. Keep container tightly closed. Wash thoroughly after handling. |
| Response | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. In case of fire: Use appropriate media for extinction. |
| Storage | Store in a well-ventilated place. Keep cool. |
| Disposal | Dispose of contents/container in accordance with local/regional/national/international regulations. See section 13 of this SDS for disposal instructions. |
| Hazard(s) not otherwise classified (HNOC) | None known. |
| Supplemental information | None. |

3. Composition/information on ingredients

Mixtures

| Chemical name | Common name and synonyms | CAS number | % |
|-------------------|--------------------------|------------|---------|
| ASPHALT, OXIDIZED | | 64742-93-4 | 40 - 60 |
| STODDARD SOLVENT | | 8052-41-3 | 40 - 60 |

Composition comments The full text for all R-phrases is displayed in Section 16 of the SDS

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. For breathing difficulties, oxygen may be necessary. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Get medical attention, if needed.

Skin contact

For hot product, immediately immerse in or flush the affected area with large amounts of cold water to dissipate heat. For minor skin contact, avoid spreading material on unaffected skin. Wash off with soap and plenty of water. If skin irritation occurs: Get medical advice/attention.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. If a contact lens is present, DO NOT delay irrigation or attempt to remove the lens. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth thoroughly. Call a POISON CENTER or doctor/physician. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and delayed

Not available.

Indication of immediate medical attention and special treatment needed

In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information

IF exposed or concerned: Get medical advice/attention. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Get medical attention if symptoms occur. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Foam. Carbon dioxide (CO₂). Water fog. Dry chemical powder.

Unsuitable extinguishing media

Do not use water jet.

Specific hazards arising from the chemical

Fire may produce irritating, corrosive and/or toxic gases.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.

Fire-fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Move containers from fire area if you can do so without risk. Do not get water inside container. Some of these materials, if spilled, may evaporate leaving a flammable residue.

Specific methods

In the event of fire and/or explosion do not breathe fumes.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep upwind. Keep out of low areas. Ventilate closed spaces before entering them. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material.

Methods and materials for containment and cleaning up

Stop the flow of material, if this is without risk. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Never return spills in original containers for re-use.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not contaminate water. If this material is spilled into navigable waters and creates a visible sheen, it is reportable to the National Response Center.

7. Handling and storage

Precautions for safe handling

Avoid heat, sparks, open flames and other ignition sources. Avoid breathing dust/fume/gas/mist/vapors/spray. Wear personal protective equipment. Do not use in areas without adequate ventilation. Avoid prolonged exposure. When using, do not eat, drink or smoke. Wash hands thoroughly after handling. Do not empty into drains. Trace amounts of hydrogen sulfide, a very highly toxic gas, may be present with this material. Keep face clear of tank and/or tank car openings.

Conditions for safe storage, including any incompatibilities

Store in a well-ventilated place. Keep container closed. Keep container dry. Keep away from food, drink and animal feedingstuffs. Keep out of reach of children. Use care in handling/storage.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components | Type | Value |
|----------------------------------|------|------------------------|
| STODDARD SOLVENT (CAS 8052-41-3) | PEL | 2900 mg/m ³ |
| | | 500 ppm |

US. ACGIH Threshold Limit Values

| Components | Type | Value |
|----------------------------------|------|---------|
| STODDARD SOLVENT (CAS 8052-41-3) | TWA | 100 ppm |

U.S. - NIOSH

| Components | Type | Value |
|------------------------------------|------|---------------------|
| ASPHALT, OXIDIZED (CAS 64742-93-4) | REL | 5 mg/m ³ |

US. NIOSH: Pocket Guide to Chemical Hazards

| Components | Type | Value |
|----------------------------------|---------|------------------------|
| STODDARD SOLVENT (CAS 8052-41-3) | Ceiling | 1800 mg/m ³ |
| | TWA | 350 mg/m ³ |

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses; chemical goggles (if splashing is possible).

Hand protection

Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style gloves.

Other

It is a good industrial hygiene practice to minimize skin contact. Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapor contact.

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Thermal hazards

Not available.

General hygiene considerations

When using, do not eat, drink or smoke. Avoid contact with eyes. Avoid contact with skin. Wash hands before breaks and immediately after handling the product. Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

| | |
|--|-----------------------------------|
| Appearance | Viscous liquid |
| Physical state | Solid. |
| Form | Liquid. |
| Color | Brown to. Black |
| Odor | Mild Petroleum Odor |
| Odor threshold | Not available. |
| pH | Not available. |
| Melting point/freezing point | No Data |
| Initial boiling point and boiling range | 300 °F (148.89 °C) |
| Flash point | 105.0 °F (40.6 °C) Tag Closed Cup |
| Evaporation rate | 70 |
| Flammability (solid, gas) | Not available. |
| Upper/lower flammability or explosive limits | |
| Flammability limit - lower (%) | 0.9 % estimated |
| Flammability limit - upper (%) | 6 % estimated |
| Explosive limit - lower (%) | Not available. |

| | |
|--|--------------------|
| Explosive limit - upper (%) | Not available. |
| Vapor pressure | < 50 psi |
| Vapor density | > 4.5 |
| Relative density | Not available. |
| Solubility(ies) | |
| Solubility (water) | Insoluble |
| Partition coefficient (n-octanol/water) | Not available. |
| Auto-ignition temperature | No Data |
| Decomposition temperature | Not available. |
| Viscosity | Not available. |
| Other information | |
| Density | 7.00 - 8.00 lb/gal |
| Flammability class | Class II |
| VOC content | ≤ 475 g/L |

10. Stability and reactivity

| | |
|---|--|
| Reactivity | The product is stable and non-reactive under normal conditions of use, storage and transport |
| Chemical stability | Stable at normal conditions. |
| Possibility of hazardous reactions | Hazardous polymerization does not occur. |
| Conditions to avoid | Heat, flames and sparks. |
| Incompatible materials | Strong oxidizing agents. |
| Hazardous decomposition products | Irritants. Carbon oxides. Sulphur oxides. |

11. Toxicological information

Information on likely routes of exposure

| | |
|---------------------|---|
| Ingestion | May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure. |
| Inhalation | Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea |
| Skin contact | Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis |
| Eye contact | May be irritating to eyes. |

Symptoms related to the physical, chemical and toxicological characteristics Not available.

Information on toxicological effects

| | |
|--|---|
| Acute toxicity | Not classified. |
| Skin corrosion/irritation | May cause defatting of the skin, but is neither an irritant nor a sensitizer. |
| Serious eye damage/eye irritation | Not classified. May be irritating to eyes. |

Respiratory or skin sensitization

| | |
|----------------------------------|------------------------|
| Respiratory sensitization | Not available. |
| Skin sensitization | Not a skin sensitizer. |

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity None of this product's components are listed by ACGIH, IARC, NIOSH, NTP or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

| | |
|------------------------------------|---|
| ASPHALT, OXIDIZED (CAS 64742-93-4) | 2A Probably carcinogenic to humans. |
| STODDARD SOLVENT (CAS 8052-41-3) | 3 Not classifiable as to carcinogenicity to humans. |

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity Not classified.

| | |
|---|---|
| Specific target organ toxicity - single exposure | Central nervous system. |
| Specific target organ toxicity - repeated exposure | Not available. |
| Aspiration hazard | Not classified. |
| Chronic effects | Prolonged exposure may cause chronic effects. |

12. Ecological information

| | |
|---|--|
| Ecotoxicity | Not expected to be harmful to aquatic organisms. |
| Persistence and degradability | Not available. |
| Bioaccumulative potential | Not available. |
| Partition coefficient n-octanol / water (logKow) | |
| STODDARD SOLVENT | 3.16 - 7.15 |
| Mobility in soil | Not available. |
| Other adverse effects | Not available. |

13. Disposal considerations

| | |
|--|--|
| Disposal instructions | Dispose of contents/container in accordance with local/regional/national/international regulations. If discarded, this product is considered a RCRA ignitable waste, D001. |
| Hazardous waste code | D001: Waste Flammable material with a flash point <140 F |
| Waste from residues / unused products | Dispose of in accordance with local regulations. |
| Contaminated packaging | Empty containers should be taken to an approved waste handling site for recycling or disposal. |

14. Transport information

| | |
|-------------------------------------|--|
| DOT | |
| UN number | UN1999 |
| UN proper shipping name | Tars, liquid |
| Transport hazard class(es) | |
| Class | Combustible Liquid |
| Subsidiary risk | - |
| Label(s) | 3 |
| Packing group | III |
| Special precautions for user | If shipped by ground in quantities LESS than 119 gallons (450 L): Not regulated as a hazardous material. |
| Special provisions | B1, B52, IB3, T4, TP1, TP29 |
| Packaging exceptions | 150 |
| Packaging non bulk | 203 |
| Packaging bulk | 242 |
| IATA | |
| UN number | UN1999 |
| UN proper shipping name | Tars, liquid |
| Transport hazard class(es) | |
| Class | 3 |
| Subsidiary risk | - |
| Packing group | III |
| Environmental hazards | No. |
| ERG Code | 3L |
| Special precautions for user | Not available. |
| Other information | |
| Passenger and cargo aircraft | Allowed. |
| Cargo aircraft only | Allowed. |

IMDG

| | |
|---|----------------|
| UN number | UN1999 |
| UN proper shipping name | Tars, liquid |
| Transport hazard class(es) | |
| Class | 3 |
| Subsidiary risk | - |
| Packing group | III |
| Environmental hazards | |
| Marine pollutant | No. |
| EmS | F-E, S-E |
| Special precautions for user | Not available. |
| Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code | Not available. |

DOT**IATA; IMDG****Further information**

If shipped by ground in quantities LESS than 119 gallons (450 L): Not regulated as a hazardous material.
If shipped by vessel in quantities less than 7.9 gallons (30 L), IMDG 2.3.2.5 exception applies: Not regulated as a hazardous material.

15. Regulatory information**US federal regulations**

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard 29 CFR 1910.1200.
CERCLA/SARA Hazardous Substances - Not applicable.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)**Hazard categories**

Immediate Hazard - No
Delayed Hazard - No
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 No
Hazardous chemical

SARA 313 (TRI reporting)
Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA)

Not regulated.

US state regulations WARNING: This product contains a chemical known to the State of California to cause cancer.

US. Massachusetts RTK - Substance List

STODDARD SOLVENT (CAS 8052-41-3)

US. New Jersey Worker and Community Right-to-Know Act

Not regulated.

US. Pennsylvania RTK - Hazardous Substances

STODDARD SOLVENT (CAS 8052-41-3)

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

Not Listed.

International Inventories

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|-----------------------------|--|------------------------|
| Australia | Australian Inventory of Chemical Substances (AICS) | Yes |
| Canada | Domestic Substances List (DSL) | Yes |
| Canada | Non-Domestic Substances List (NDSL) | No |
| China | Inventory of Existing Chemical Substances in China (IECSC) | Yes |
| Europe | European Inventory of Existing Commercial Chemical Substances (EINECS) | Yes |
| Europe | European List of Notified Chemical Substances (ELINCS) | No |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | Yes |
| Korea | Existing Chemicals List (ECL) | Yes |
| New Zealand | New Zealand Inventory | Yes |
| Philippines | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | Yes |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes |

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 08-01-2015

Version # 03

References ACGIH
EPA: AQUIRE database
NLM: Hazardous Substances Data Base
US. IARC Monographs on Occupational Exposures to Chemical Agents
HSDB® - Hazardous Substances Data Bank
IARC Monographs. Overall Evaluation of Carcinogenicity
National Toxicology Program (NTP) Report on Carcinogens
ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

Revision Information

New email address