

SECTION 1: IDENTIFICATION

Product Identifier

Product Form: Mixture

Product Name: Pro Color Finish Resin

Synonyms: Pro Color Finish - Gray, Beige, White, Blue, Terracotta, and Yellow

Intended Use of the Product

Use of the Substance/Mixture: Liquid-applied Waterproofing System - Component. For professional use only.

Name, Address, and Telephone of the Responsible Party

Company

Siplast, Inc.
 1000 East Rochelle Blvd
 Irving, TX 75062
 T 800-922-8800
www.siplast.com

Manufacturer

Siplast, Inc.
 35 McClelland Blvd
 Arkadelphia, AR 71923
 T 870-246-9000

Emergency Telephone Number

Emergency Number : 800-424-9300 (CHEMTREC)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US)

Flam. Liq. 2	H225
Skin Irrit. 2	H315
Eye Irrit. 2A	H319
Resp. Sens. 1	H334
Skin Sens. 1	H317
Repr. 1B	H360
STOT SE 3	H335
Aquatic Acute 3	H402
Aquatic Chronic 2	H411

Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)



Signal Word (GHS-US)

: Danger

Hazard Statements (GHS-US)

: H225 - Highly flammable liquid and vapor.
 H315 - Causes skin irritation.
 H317 - May cause an allergic skin reaction.
 H319 - Causes serious eye irritation.
 H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 H335 - May cause respiratory irritation.
 H360 - May damage fertility or the unborn child.
 H402 - Harmful to aquatic life.
 H411 - Toxic to aquatic life with long lasting effects.

Precautionary Statements (GHS-US)

: P201 - Obtain special instructions before use.
 P202 - Do not handle until all safety precautions have been read and understood.
 P210 - Keep away from heat, sparks, open flames, hot surfaces. - No smoking.
 P233 - Keep container tightly closed.
 P240 - Ground/bond container and receiving equipment.
 P241 - Use explosion-proof electrical, ventilating, and lighting equipment.
 P242 - Use only non-sparking tools.
 P243 - Take precautionary measures against static discharge.

P261 - Avoid breathing vapors, mist, spray.
 P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.
 P271 - Use only outdoors or in a well-ventilated area.
 P272 - Contaminated work clothing must not be allowed out of the workplace.
 P273 - Avoid release to the environment.
 P280 - Wear protective gloves, protective clothing, eye protection, face protection, respiratory protection.
 P284 - [In case of inadequate ventilation] wear respiratory protection.
 P302+P352 - If on skin: Wash with plenty of water.
 P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P304+P340 - IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing.
 P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308+P313 - If exposed or concerned: Get medical advice/attention.
 P312 - Call a poison center/doctor if you feel unwell.
 P321 - Specific treatment (see section 4).
 P332+P313 - If skin irritation occurs: Get medical advice/attention.
 P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
 P337+P313 - If eye irritation persists: Get medical advice/attention.
 P342+P311 - If experiencing respiratory symptoms: Call a poison center/doctor.
 P362 - Take off contaminated clothing and wash before reuse.
 P362+P364 - Take off contaminated clothing and wash it before reuse.
 P370+P378 - In case of fire: Use appropriate media to extinguish.
 P391 - Collect spillage.
 P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
 P403+P235 - Store in a well-ventilated place. Keep cool.
 P405 - Store locked up.
 P501 - Dispose of contents/container according to local, regional, national, territorial, provincial, and international regulations.

Other Hazards

Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions. Flammable vapors can accumulate in head space of closed systems.

Unknown Acute Toxicity (GHS-US) Not available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Name	Product Identifier	% (w/w)	Classification (GHS-US)
Methyl methacrylate	(CAS No) 80-62-6	30 - 60	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Eye Irrit. 2B, H320 Resp. Sens. 1, H334 Skin Sens. 1, H317 STOT SE 3, H335 Aquatic Acute 3, H402
2-Ethylhexyl acrylate	(CAS No) 103-11-7	10 - 30	Flam. Liq. 4, H227 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1, H317 STOT SE 3, H336 Aquatic Acute 3, H402 Aquatic Chronic 3, H412
Iron oxide (Fe2O3)	(CAS No) 1309-37-1	0.1 - 7	Not classified

Titanium dioxide	(CAS No) 13463-67-7	0.1 - 7	Not classified
2-Propenoic acid, 2-methyl-, oxybis(2,1-ethanediylxy-2,1-ethanediyl) ester	(CAS No) 109-17-1	1 - 2	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1, H317
2,2,4-Trimethyl-1,3-pentanediol diisobutyrate	(CAS No) 6846-50-0	0.1 - 1	Aquatic Acute 2, H401 Aquatic Chronic 3, H412
2-Propanol, 1,1'-[(4-methylphenyl)imino]bis-	(CAS No) 38668-48-3	0.1 - 1	Acute Tox. 2 (Oral), H300 Eye Irrit. 2A, H319 Aquatic Acute 3, H402 Aquatic Chronic 3, H412
Aluminum hydroxide (Al(OH) ₃)	(CAS No) 21645-51-2	0 - 1	Not classified
Xylenes (o-, m-, p- isomers)	(CAS No) 1330-20-7	0.1 - 1	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
2-Hydroxy-4-methoxybenzophenone	(CAS No) 131-57-7	0,1 – 0.5	Comb. Dust, H232 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Butyl methacrylate	(CAS No) 97-88-1	0 – 0.5	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT SE 3, H335 Aquatic Acute 3, H402
Propylene glycol monomethyl ether acetate	(CAS No) 108-65-6	0 – 0.5	Flam. Liq. 3, H226
n-Butyl acetate	(CAS No) 123-86-4	0 – 0.5	Flam. Liq. 3, H226 STOT SE 3, H336 Aquatic Acute 3, H402
Ethylbenzene	(CAS No) 100-41-4	0 – 0.5	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation:vapour), H332 Eye Irrit. 2B, H320 Carc. 2, H351 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 3, H412

Multiple WHMIS ranges as prescribed by the Controlled Products Regulations have been utilized due to varying composition.
Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medical advice/attention.

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor/physician if you feel unwell.

Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention.

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persist.

Ingestion: Rinse mouth. Do NOT induce vomiting. Seek medical attention.

Most Important Symptoms and Effects Both Acute and Delayed

General: Eye irritation. Skin irritation. May cause an allergic skin reaction. Inhalation may cause allergic respiratory reaction with asthma-like symptoms and difficulty breathing. Irritation of respiratory tract. Causes serious eye irritation. Suspected of causing cancer.

Inhalation: May cause respiratory irritation. Exposure may produce an allergic reaction. May cause drowsiness or dizziness. Inhalation may cause immediate severe irritation progressing quickly to chemical burns.

Skin Contact: Causes skin irritation. May cause an allergic skin reaction.

Eye Contact: Causes eye irritation.

Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: Suspected of causing cancer.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Dry chemical powder, foam, carbon dioxide (CO₂).

Unsuitable Extinguishing Media: Do not use extinguishing media containing water.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Highly flammable liquid and vapor.

Explosion Hazard: May form flammable/explosive vapor-air mixture.

Reactivity: Product may polymerize at 60°C (>140°F), causing an exothermic reaction which may cause container damage or fire. May react with peroxides, oxidizers, and incompatibilities.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Nitrogen oxides. Hydrocarbons. Black smoke.

Other Information: Do not allow run-off from fire fighting to enter drains or water courses.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Use special care to avoid static electric charges. Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Avoid all eyes and skin contact and do not breathe vapor and mist. Do not allow product to spread into the environment. Handle in accordance with good industrial hygiene and safety practice.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection. Use appropriate personal protection equipment (PPE).

Emergency Procedures: Ventilate area.

Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clear up spills immediately and dispose of waste safely. Absorb and/or contain spill with inert material, then place in suitable container. Do not take up in combustible material such as: saw dust or cellulosic material. Contact competent authorities after a spill.

Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection.



Pro Color Finish Resin

Safety Data Sheet

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Additional Hazards When Processed: Handle empty containers with care because residual vapors are flammable. Product may polymerize at 60°C (>140°F), causing an exothermic reaction which may cause container damage or fire. May react with peroxides, oxidizers, and incompatibilities. When heated to decomposition, emits toxic fumes.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Wash hands and forearms thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product.

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment.

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep in fireproof place. Keep/Store away from extremely high or low temperatures, ignition sources, combustible materials, heat, direct sunlight, incompatible materials.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers.

Specific End Use(s)

Liquid-applied Waterproofing System - Component.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Methyl methacrylate (80-62-6)		
Mexico	OEL TWA (mg/m ³)	410 mg/m ³
Mexico	OEL TWA (ppm)	100 ppm
Mexico	OEL STEL (mg/m ³)	510 mg/m ³
Mexico	OEL STEL (ppm)	125 ppm
USA ACGIH	ACGIH TWA (ppm)	50 ppm
USA ACGIH	ACGIH STEL (ppm)	100 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	410 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	410 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	100 ppm
USA IDLH	US IDLH (ppm)	1000 ppm
Alberta	OEL STEL (mg/m ³)	410 mg/m ³
Alberta	OEL STEL (ppm)	100 ppm
Alberta	OEL TWA (mg/m ³)	205 mg/m ³
Alberta	OEL TWA (ppm)	50 ppm
British Columbia	OEL STEL (ppm)	100 ppm
British Columbia	OEL TWA (ppm)	50 ppm
Manitoba	OEL STEL (ppm)	100 ppm
Manitoba	OEL TWA (ppm)	50 ppm
New Brunswick	OEL TWA (mg/m ³)	410 mg/m ³
New Brunswick	OEL TWA (ppm)	100 ppm
Newfoundland & Labrador	OEL STEL (ppm)	100 ppm
Newfoundland & Labrador	OEL TWA (ppm)	50 ppm
Nova Scotia	OEL STEL (ppm)	100 ppm
Nova Scotia	OEL TWA (ppm)	50 ppm
Nunavut	OEL STEL (mg/m ³)	510 mg/m ³
Nunavut	OEL STEL (ppm)	125 ppm
Nunavut	OEL TWA (mg/m ³)	410 mg/m ³
Nunavut	OEL TWA (ppm)	100 ppm
Northwest Territories	OEL STEL (mg/m ³)	510 mg/m ³



Pro Color Finish Resin Safety Data Sheet

Northwest Territories	OEL STEL (ppm)	125 ppm
Northwest Territories	OEL TWA (mg/m ³)	410 mg/m ³
Northwest Territories	OEL TWA (ppm)	100 ppm
Ontario	OEL STEL (ppm)	100 ppm
Ontario	OEL TWA (ppm)	50 ppm
Prince Edward Island	OEL STEL (ppm)	100 ppm
Prince Edward Island	OEL TWA (ppm)	50 ppm
Québec	VEMP (mg/m ³)	205 mg/m ³
Québec	VEMP (ppm)	50 ppm
Saskatchewan	OEL STEL (ppm)	100 ppm
Saskatchewan	OEL TWA (ppm)	50 ppm
Yukon	OEL STEL (mg/m ³)	510 mg/m ³
Yukon	OEL STEL (ppm)	125 ppm
Yukon	OEL TWA (mg/m ³)	410 mg/m ³
Yukon	OEL TWA (ppm)	100 ppm
Ethylbenzene (100-41-4)		
Mexico	OEL TWA (mg/m ³)	435 mg/m ³
Mexico	OEL TWA (ppm)	100 ppm
Mexico	OEL STEL (mg/m ³)	545 mg/m ³
Mexico	OEL STEL (ppm)	125 ppm
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	435 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	435 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	100 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m ³)	545 mg/m ³
USA NIOSH	NIOSH REL (STEL) (ppm)	125 ppm
USA IDLH	US IDLH (ppm)	800 ppm (10% LEL)
Alberta	OEL STEL (mg/m ³)	543 mg/m ³
Alberta	OEL STEL (ppm)	125 ppm
Alberta	OEL TWA (mg/m ³)	434 mg/m ³
Alberta	OEL TWA (ppm)	100 ppm
British Columbia	OEL TWA (ppm)	20 ppm
Manitoba	OEL TWA (ppm)	20 ppm
New Brunswick	OEL STEL (mg/m ³)	543 mg/m ³
New Brunswick	OEL STEL (ppm)	125 ppm
New Brunswick	OEL TWA (mg/m ³)	434 mg/m ³
New Brunswick	OEL TWA (ppm)	100 ppm
Newfoundland & Labrador	OEL TWA (ppm)	20 ppm
Nova Scotia	OEL TWA (ppm)	20 ppm
Nunavut	OEL STEL (mg/m ³)	542 mg/m ³
Nunavut	OEL STEL (ppm)	125 ppm
Nunavut	OEL TWA (mg/m ³)	434 mg/m ³
Nunavut	OEL TWA (ppm)	100 ppm
Northwest Territories	OEL STEL (mg/m ³)	542 mg/m ³
Northwest Territories	OEL STEL (ppm)	125 ppm
Northwest Territories	OEL TWA (mg/m ³)	434 mg/m ³
Northwest Territories	OEL TWA (ppm)	100 ppm
Ontario	OEL TWA (ppm)	20 ppm
Prince Edward Island	OEL TWA (ppm)	20 ppm
Québec	VECD (mg/m ³)	543 mg/m ³



Pro Color Finish Resin Safety Data Sheet

Québec	VECD (ppm)	125 ppm
Québec	VEMP (mg/m ³)	434 mg/m ³
Québec	VEMP (ppm)	100 ppm
Saskatchewan	OEL STEL (ppm)	125 ppm
Saskatchewan	OEL TWA (ppm)	100 ppm
Yukon	OEL STEL (mg/m ³)	545 mg/m ³
Yukon	OEL STEL (ppm)	125 ppm
Yukon	OEL TWA (mg/m ³)	435 mg/m ³
Yukon	OEL TWA (ppm)	100 ppm
Propylene glycol monomethyl ether acetate (108-65-6)		
British Columbia	OEL STEL (ppm)	75 ppm
British Columbia	OEL TWA (ppm)	50 ppm
Ontario	OEL TWA (mg/m ³)	270 mg/m ³
Ontario	OEL TWA (ppm)	50 ppm
n-Butyl acetate (123-86-4)		
Mexico	OEL TWA (mg/m ³)	710 mg/m ³
Mexico	OEL TWA (ppm)	150 ppm
Mexico	OEL STEL (mg/m ³)	950 mg/m ³
Mexico	OEL STEL (ppm)	200 ppm
USA ACGIH	ACGIH TWA (ppm)	150 ppm
USA ACGIH	ACGIH STEL (ppm)	200 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	710 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	150 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	710 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	150 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m ³)	950 mg/m ³
USA NIOSH	NIOSH REL (STEL) (ppm)	200 ppm
USA IDLH	US IDLH (ppm)	1700 ppm (10% LEL)
Alberta	OEL STEL (mg/m ³)	950 mg/m ³
Alberta	OEL STEL (ppm)	200 ppm
Alberta	OEL TWA (mg/m ³)	713 mg/m ³
Alberta	OEL TWA (ppm)	150 ppm
British Columbia	OEL TWA (ppm)	20 ppm
Manitoba	OEL STEL (ppm)	200 ppm
Manitoba	OEL TWA (ppm)	150 ppm
New Brunswick	OEL STEL (mg/m ³)	950 mg/m ³
New Brunswick	OEL STEL (ppm)	200 ppm
New Brunswick	OEL TWA (mg/m ³)	713 mg/m ³
New Brunswick	OEL TWA (ppm)	150 ppm
Newfoundland & Labrador	OEL STEL (ppm)	200 ppm
Newfoundland & Labrador	OEL TWA (ppm)	150 ppm
Nova Scotia	OEL STEL (ppm)	200 ppm
Nova Scotia	OEL TWA (ppm)	150 ppm
Nunavut	OEL STEL (mg/m ³)	950 mg/m ³
Nunavut	OEL STEL (ppm)	200 ppm
Nunavut	OEL TWA (mg/m ³)	713 mg/m ³
Nunavut	OEL TWA (ppm)	150 ppm
Northwest Territories	OEL STEL (mg/m ³)	950 mg/m ³
Northwest Territories	OEL STEL (ppm)	200 ppm
Northwest Territories	OEL TWA (mg/m ³)	713 mg/m ³
Northwest Territories	OEL TWA (ppm)	150 ppm



Pro Color Finish Resin Safety Data Sheet

Ontario	OEL STEL (ppm)	200 ppm
Ontario	OEL TWA (ppm)	150 ppm
Prince Edward Island	OEL STEL (ppm)	200 ppm
Prince Edward Island	OEL TWA (ppm)	150 ppm
Québec	VECD (mg/m ³)	950 mg/m ³
Québec	VECD (ppm)	200 ppm
Québec	VEMP (mg/m ³)	713 mg/m ³
Québec	VEMP (ppm)	150 ppm
Saskatchewan	OEL STEL (ppm)	200 ppm
Saskatchewan	OEL TWA (ppm)	150 ppm
Yukon	OEL STEL (mg/m ³)	950 mg/m ³
Yukon	OEL STEL (ppm)	200 ppm
Yukon	OEL TWA (mg/m ³)	710 mg/m ³
Yukon	OEL TWA (ppm)	150 ppm
Iron oxide (Fe₂O₃) (1309-37-1)		
Mexico	OEL TWA (mg/m ³)	5 mg/m ³
Mexico	OEL STEL (mg/m ³)	10 mg/m ³
USA ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³ (respirable fraction)
USA OSHA	OSHA PEL (TWA) (mg/m ³)	10 mg/m ³ (fume) 15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	5 mg/m ³ (dust and fume)
USA IDLH	US IDLH (mg/m ³)	2500 mg/m ³ (dust and fume)
Alberta	OEL TWA (mg/m ³)	5 mg/m ³ (respirable)
British Columbia	OEL STEL (mg/m ³)	10 mg/m ³ (fume)
British Columbia	OEL TWA (mg/m ³)	10 mg/m ³ (total particulate matter containing no Asbestos and <1% Crystalline silica-total particulate)
Manitoba	OEL TWA (mg/m ³)	5 mg/m ³ (respirable fraction)
New Brunswick	OEL TWA (mg/m ³)	5 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica, dust and fume)
Newfoundland & Labrador	OEL TWA (mg/m ³)	5 mg/m ³ (respirable fraction)
Nova Scotia	OEL TWA (mg/m ³)	5 mg/m ³ (respirable fraction)
Nunavut	OEL TWA (mg/m ³)	5 mg/m ³ (respirable mass)
Northwest Territories	OEL TWA (mg/m ³)	5 mg/m ³ (respirable mass)
Ontario	OEL TWA (mg/m ³)	5 mg/m ³ (respirable)
Prince Edward Island	OEL TWA (mg/m ³)	5 mg/m ³ (respirable fraction)
Québec	VEMP (mg/m ³)	5 mg/m ³ (dust and fume)
Saskatchewan	OEL STEL (mg/m ³)	10 mg/m ³ (dust and fume)
Saskatchewan	OEL TWA (mg/m ³)	5 mg/m ³ (dust and fume)
Yukon	OEL STEL (mg/m ³)	10 mg/m ³ (fume)
Yukon	OEL TWA (mg/m ³)	5 mg/m ³ (fume)
Xylenes (o-, m-, p- isomers) (1330-20-7)		
Mexico	OEL TWA (mg/m ³)	435 mg/m ³
Mexico	OEL TWA (ppm)	100 ppm
Mexico	OEL STEL (mg/m ³)	655 mg/m ³
Mexico	OEL STEL (ppm)	150 ppm
USA ACGIH	ACGIH TWA (ppm)	100 ppm
USA ACGIH	ACGIH STEL (ppm)	150 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	435 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm
Alberta	OEL STEL (mg/m ³)	651 mg/m ³



Pro Color Finish Resin Safety Data Sheet

Alberta	OEL STEL (ppm)	150 ppm
Alberta	OEL TWA (mg/m ³)	434 mg/m ³
Alberta	OEL TWA (ppm)	100 ppm
British Columbia	OEL STEL (ppm)	150 ppm
British Columbia	OEL TWA (ppm)	100 ppm
Manitoba	OEL STEL (ppm)	150 ppm
Manitoba	OEL TWA (ppm)	100 ppm
New Brunswick	OEL STEL (mg/m ³)	651 mg/m ³
New Brunswick	OEL STEL (ppm)	150 ppm
New Brunswick	OEL TWA (mg/m ³)	434 mg/m ³
New Brunswick	OEL TWA (ppm)	100 ppm
Newfoundland & Labrador	OEL STEL (ppm)	150 ppm
Newfoundland & Labrador	OEL TWA (ppm)	100 ppm
Nova Scotia	OEL STEL (ppm)	150 ppm
Nova Scotia	OEL TWA (ppm)	100 ppm
Nunavut	OEL STEL (mg/m ³)	652 mg/m ³
Nunavut	OEL STEL (ppm)	150 ppm
Nunavut	OEL TWA (mg/m ³)	434 mg/m ³
Nunavut	OEL TWA (ppm)	100 ppm
Northwest Territories	OEL STEL (mg/m ³)	652 mg/m ³
Northwest Territories	OEL STEL (ppm)	150 ppm
Northwest Territories	OEL TWA (mg/m ³)	434 mg/m ³
Northwest Territories	OEL TWA (ppm)	100 ppm
Ontario	OEL STEL (ppm)	150 ppm
Ontario	OEL TWA (ppm)	100 ppm
Prince Edward Island	OEL STEL (ppm)	150 ppm
Prince Edward Island	OEL TWA (ppm)	100 ppm
Québec	VECD (mg/m ³)	651 mg/m ³
Québec	VECD (ppm)	150 ppm
Québec	VEMP (mg/m ³)	434 mg/m ³
Québec	VEMP (ppm)	100 ppm
Saskatchewan	OEL STEL (ppm)	150 ppm
Saskatchewan	OEL TWA (ppm)	100 ppm
Yukon	OEL STEL (mg/m ³)	650 mg/m ³
Yukon	OEL STEL (ppm)	150 ppm
Yukon	OEL TWA (mg/m ³)	435 mg/m ³
Yukon	OEL TWA (ppm)	100 ppm

Titanium dioxide (13463-67-7)


Mexico	OEL TWA (mg/m ³)	10 mg/m ³
Mexico	OEL STEL (mg/m ³)	20 mg/m ³
USA ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust)
USA IDLH	US IDLH (mg/m ³)	5000 mg/m ³
Alberta	OEL TWA (mg/m ³)	10 mg/m ³
British Columbia	OEL TWA (mg/m ³)	10 mg/m ³ (total dust)
Manitoba	OEL TWA (mg/m ³)	10 mg/m ³
New Brunswick	OEL TWA (mg/m ³)	10 mg/m ³
Newfoundland & Labrador	OEL TWA (mg/m ³)	10 mg/m ³
Nova Scotia	OEL TWA (mg/m ³)	10 mg/m ³
Nunavut	OEL TWA (mg/m ³)	5 mg/m ³ (respirable mass)
Northwest Territories	OEL TWA (mg/m ³)	5 mg/m ³ (respirable mass)

Ontario	OEL TWA (mg/m ³)	10 mg/m ³
Prince Edward Island	OEL TWA (mg/m ³)	10 mg/m ³
Québec	VEMP (mg/m ³)	10 mg/m ³ (containing no Asbestos and <1% Crystalline silica-total dust)
Saskatchewan	OEL STEL (mg/m ³)	20 mg/m ³
Saskatchewan	OEL TWA (mg/m ³)	10 mg/m ³
Yukon	OEL STEL (mg/m ³)	20 mg/m ³
Yukon	OEL TWA (mg/m ³)	30 mppcf
Butyl methacrylate (97-88-1)		
British Columbia	OEL TWA (ppm)	50 ppm

Exposure Controls

Appropriate Engineering Controls: Ensure all national/local regulations are observed. Gas detectors should be used when flammable gases/vapors may be released. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof equipment. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment: Protective clothing. Gloves. Insufficient ventilation: wear respiratory protection. Protective goggles.



Materials for Protective Clothing: Chemically resistant materials and fabrics. Wear fire/flamm resistant/retardant clothing.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical goggles or safety glasses.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: Use NIOSH-approved air-purifying or supplied-air respirator where airborne concentrations of vapor or mist are expected to exceed exposure limits.

Thermal Hazard Protection: Wear suitable protective clothing.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Gray, Beige, White & Blue
Odor	: Methyl methacrylate
Odor Threshold	: Not available
pH	: Not available
Evaporation Rate	: Not available
Melting Point	: Not available
Freezing Point	: Not available
Boiling Point	: Not available
Flash Point	: > 10 °C (50.00 °F)
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: 1000 hPa @50°C (122°F)
Relative Vapor Density at 20 °C	: Not available
Relative Density	: Not available
Density	: 1.05 g/ml (@21°C (69.8°F))
Specific Gravity	: Not available

Solubility	: Insoluble in water
Partition Coefficient: N-octanol/water	: Not available
Viscosity	: Efflux time 25 - 30 sec @20°C (68°F)
Explosion Data – Sensitivity to Mechanical Impact	: Not expected to present an explosion hazard due to mechanical impact.
Explosion Data – Sensitivity to Static Discharge	: Static discharge could act as an ignition source.
Percent VOC Content Catalyzed	: Less than 50 grams per liter.

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Product may polymerize at 60°C (>140°F), causing an exothermic reaction which may cause container damage or fire. May react with peroxides, oxidizers, and incompatibilities.

Chemical Stability: Highly flammable liquid and vapor. May form flammable/explosive vapor-air mixture.

Possibility of Hazardous Reactions: Hazardous polymerization may occur.

Conditions to Avoid: Direct sunlight. Extremely high or low temperatures. Heat. Ignition sources. Incompatible materials.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers.

Hazardous Decomposition Products: Carbon oxides (CO, CO₂). May release flammable gases. Toxic gases. Nitrogen oxides. Hydrocarbons.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Not classified

LD50 and LC50 Data: Not available

Skin Corrosion/Irritation: Causes skin irritation.

Serious Eye Damage/Irritation: Causes serious eye irritation.

Respiratory or Skin Sensitization: May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

Germ Cell Mutagenicity: Not classified

Teratogenicity: Not available

Carcinogenicity: Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: May damage fertility or the unborn child.

Specific Target Organ Toxicity (Single Exposure): May cause respiratory irritation.

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: May cause respiratory irritation. Exposure may produce an allergic reaction. May cause drowsiness or dizziness. Inhalation may cause immediate severe irritation progressing quickly to chemical burns.

Symptoms/Injuries After Skin Contact: Causes skin irritation. May cause an allergic skin reaction.

Symptoms/Injuries After Eye Contact: Causes eye irritation.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: Suspected of causing cancer.

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

2-Propanol, 1,1'-[(4-methylphenyl)imino]bis- (38668-48-3)	
LD50 Oral Rat	25 mg/kg
Methyl methacrylate (80-62-6)	
LD50 Oral Rat	7900 mg/kg
LC50 Inhalation Rat	4632 ppm/4h
2-Ethylhexyl acrylate (103-11-7)	
LD50 Oral Rat	4435 mg/kg
LD50 Dermal Rabbit	7522 mg/kg
2,2,4-Trimethyl-1,3-pentanediol diisobutyrate (6846-50-0)	
LD50 Oral Rat	> 3200 mg/kg

Ethylbenzene (100-41-4)	
LD50 Oral Rat	3500 mg/kg
LD50 Dermal Rabbit	15400 mg/kg
LC50 Inhalation Rat	17.2 mg/l/4h (Exposure time: 4 h)
Propylene glycol monomethyl ether acetate (108-65-6)	
LD50 Oral Rat	8532 mg/kg
LD50 Dermal Rabbit	> 5 g/kg
n-Butyl acetate (123-86-4)	
LD50 Oral Rat	14.13 mg/kg
LD50 Dermal Rabbit	> 17600 mg/kg
LC50 Inhalation Rat	390 ppm/4h
Iron oxide (Fe2O3) (1309-37-1)	
LD50 Oral Rat	> 10000 mg/kg
Xylenes (o-, m-, p- isomers) (1330-20-7)	
LD50 Oral Rat	3500 mg/kg
LD50 Dermal Rabbit	> 4350 mg/kg
LC50 Inhalation Rat	47635 mg/l/4h (Exposure time: 4 h)
LC50 Inhalation Rat	6247 ppm/4h (species: Sprague-Dawley)
Titanium dioxide (13463-67-7)	
LD50 Oral Rat	> 10000 mg/kg
Aluminum hydroxide (Al(OH)3) (21645-51-2)	
LD50 Oral Rat	> 5000 mg/kg
Butyl methacrylate (97-88-1)	
LD50 Dermal Rabbit	10181 mg/kg
LC50 Inhalation Rat	4910 ppm/4h
Methyl methacrylate (80-62-6)	
IARC Group	3
2-Ethylhexyl acrylate (103-11-7)	
IARC Group	3
Ethylbenzene (100-41-4)	
IARC Group	2B
National Toxicity Program (NTP) Status	Evidence of Carcinogenicity.
Iron oxide (Fe2O3) (1309-37-1)	
IARC Group	3
Xylenes (o-, m-, p- isomers) (1330-20-7)	
IARC Group	3
Titanium dioxide (13463-67-7)	
IARC Group	2B

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Ecology - General: Harmful to aquatic life.

2-Propanol, 1,1'-[(4-methylphenyl)imino]bis- (38668-48-3)	
LC50 Fish 1	17 mg/l
EC50 Daphnia 1	28.8 mg/l
LC 50 Fish 2	>=

Methyl methacrylate (80-62-6)	
LC50 Fish 1	243 - 275 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	69 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC 50 Fish 2	125.5 - 190.7 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
2-Ethylhexyl acrylate (103-11-7)	
EC50 Daphnia 1	17.45 mg/l (Exposure time: 48 h - Species: Daphnia magna)
2,2,4-Trimethyl-1,3-pentanediol diisobutyrate (6846-50-0)	
LC50 Fish 1	> 1.55 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	> 1.46 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Ethylbenzene (100-41-4)	
LC50 Fish 1	11.0 - 18.0 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 1	1.8 - 2.4 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC 50 Fish 2	4.2 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static])
Propylene glycol monomethyl ether acetate (108-65-6)	
LC50 Fish 1	161 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	> 500 mg/l (Exposure time: 48 h - Species: Daphnia magna)
n-Butyl acetate (123-86-4)	
LC50 Fish 1	100 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
LC 50 Fish 2	17 - 19 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
Xylenes (o-, m-, p- isomers) (1330-20-7)	
LC50 Fish 1	3.3 mg/l
EC50 Daphnia 1	3.82 mg/l (Exposure time: 48 h - Species: water flea)
LC 50 Fish 2	2.661 (2.661 - 4.093) mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
Butyl methacrylate (97-88-1)	
LC50 Fish 1	11 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	32 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Persistence and Degradability Not available	
Bioaccumulative Potential	
Pro Color Finish Resin	
Bioaccumulative Potential	Not established.
Methyl methacrylate (80-62-6)	
Log Pow	0.7
2-Ethylhexyl acrylate (103-11-7)	
Log Pow	4.64 (at 25 °C)
Ethylbenzene (100-41-4)	
BCF Fish 1	15
Log Pow	3.118
Propylene glycol monomethyl ether acetate (108-65-6)	
Log Pow	0.43
n-Butyl acetate (123-86-4)	
Log Pow	1.81 (at 23 °C)
Xylenes (o-, m-, p- isomers) (1330-20-7)	
BCF Fish 1	0.6 (0.6 - 15)
Log Pow	2.77 - 3.15
Butyl methacrylate (97-88-1)	
Log Pow	2.26

Mobility in Soil Not available

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

Additional Information: Handle empty containers with care because residual vapors are flammable.

SECTION 14: TRANSPORT INFORMATION

In Accordance with DOT

Proper Shipping Name : PAINT
 Hazard Class : 3
 Identification Number : UN1263
 Label Codes : 3
 Packing Group : II
 ERG Number : 128



In Accordance with IMDG

Proper Shipping Name : PAINT
 Hazard Class : 3
 Identification Number : UN1263
 Packing Group : II
 Label Codes : 3
 EmS-No. (Fire) : F-E
 EmS-No. (Spillage) : S-E



In Accordance with IATA

Proper Shipping Name : PAINT
 Packing Group : II
 Identification Number : UN1263
 Hazard Class : 3
 Label Codes : 3
 ERG Code (IATA) : 3L



In Accordance with TDG

Proper Shipping Name : PAINT
 Packing Group : II
 Hazard Class : 3
 Identification Number : UN1263
 Label Codes : 3



SECTION 15: REGULATORY INFORMATION

US Federal Regulations

Pro Color Finish Resin	
SARA Section 311/312 Hazard Classes	Fire hazard; Immediate (acute) health hazard; Delayed (chronic) health hazard
2-Propanol, 1,1'-[(4-methylphenyl)imino]bis- (38668-48-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Methyl methacrylate (80-62-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on United States SARA Section 313	
SARA Section 313 - Emission Reporting	1.0 %
2-Ethylhexyl acrylate (103-11-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	



Pro Color Finish Resin Safety Data Sheet

2,2,4-Trimethyl-1,3-pentanediol diisobutyrate (6846-50-0)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Ethylbenzene (100-41-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on United States SARA Section 313	
RQ (Reportable Quantity, Section 304 of EPA's List of Lists):	1000 lb
SARA Section 313 - Emission Reporting	0.1 %
Propylene glycol monomethyl ether acetate (108-65-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
SARA Section 311/312 Hazard Classes	Fire hazard
2-Propenoic acid, 2-methyl-, oxybis(2,1-ethanedioxy-2,1-ethanediyl) ester (109-17-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
n-Butyl acetate (123-86-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
Iron oxide (Fe2O3) (1309-37-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
2-Hydroxy-4-methoxybenzophenone (131-57-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Xylenes (o-, m-, p- isomers) (1330-20-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on United States SARA Section 313	
RQ (Reportable Quantity, Section 304 of EPA's List of Lists):	100 lb
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard Fire hazard Immediate (acute) health hazard
SARA Section 313 - Emission Reporting	1.0 %
Titanium dioxide (13463-67-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Aluminum hydroxide (Al(OH)3) (21645-51-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
SARA Section 313 - Emission Reporting	1.0 %
Butyl methacrylate (97-88-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
US State Regulations	
Ethylbenzene (100-41-4)	
U.S. - California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of California to cause cancer.
Titanium dioxide (13463-67-7)	
U.S. - California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of California to cause cancer.
Methyl methacrylate (80-62-6)	
U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728)	
U.S. - Colorado - Hazardous Wastes - Discarded Chemical Products, Off-Specification Species, Container and Spill Residues	
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)	
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)	
U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities	
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations	



Pro Color Finish Resin Safety Data Sheet

U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)
U.S. - Idaho - Occupational Exposure Limits - TWAs
U.S. - Illinois - Toxic Air Contaminants
U.S. - Louisiana - Reportable Quantity List for Pollutants
U.S. - Maine - Air Pollutants - Hazardous Air Pollutants
U.S. - Massachusetts - Allowable Ambient Limits (AALs)
U.S. - Massachusetts - Allowable Threshold Concentrations (ATCs)
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2
U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2
RTK - U.S. - Massachusetts - Right To Know List
U.S. - Massachusetts - Threshold Effects Exposure Limits (TEELs)
U.S. - Massachusetts - Toxics Use Reduction Act
U.S. - Michigan - Occupational Exposure Limits - TWAs
U.S. - Michigan - Polluting Materials List
U.S. - Minnesota - Chemicals of High Concern
U.S. - Minnesota - Hazardous Substance List
U.S. - Minnesota - Permissible Exposure Limits - TWAs
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual
U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances
U.S. - New Jersey - Environmental Hazardous Substances List
RTK - U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New Jersey - Special Health Hazards Substances List
U.S. - New York - Occupational Exposure Limits - TWAs
U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 1-Hour
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour
U.S. - North Dakota - Hazardous Wastes - Discarded Chemical Products, Off-Specification Species, Container and Spill Residues
U.S. - Oregon - Permissible Exposure Limits - TWAs
RTK - U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
RTK - U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - 24-Hour
U.S. - South Carolina - Toxic Air Pollutants - Maximum Allowable Concentrations
U.S. - South Carolina - Toxic Air Pollutants - Pollutant Categories
U.S. - Tennessee - Occupational Exposure Limits - TWAs
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term
U.S. - Vermont - Hazardous Waste - Hazardous Constituents
U.S. - Vermont - Permissible Exposure Limits - TWAs
U.S. - Washington - Dangerous Waste - Dangerous Waste Constituents List
U.S. - Washington - Dangerous Waste - Discarded Chemical Products List
U.S. - Washington - Permissible Exposure Limits - STELs
U.S. - Washington - Permissible Exposure Limits - TWAs
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 25 Feet to Less Than 40 Feet
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 40 Feet to Less Than 75 Feet
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 75 Feet or Greater
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights Less Than 25 Feet

2-Ethylhexyl acrylate (103-11-7)

U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2
U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity



Pro Color Finish Resin Safety Data Sheet

U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2
RTK - U.S. - Massachusetts - Right To Know List
RTK - U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New Jersey - Special Health Hazards Substances List
RTK - U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term

2,2,4-Trimethyl-1,3-pentanediol diisobutyrate (6846-50-0)

U.S. - Minnesota - Chemicals of High Concern
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term

Ethylbenzene (100-41-4)

U.S. - California - Priority Toxic Pollutants - Human Health Criteria
U.S. - California - SCAQMD - Toxic Air Contaminants - Carcinogens
U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Chronic
U.S. - California - SDAPCD - Toxic Air Contaminants - Carcinogenic Impacts Must Be Calculated
U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728)
U.S. - Colorado - Groundwater Quality Standards
U.S. - Colorado - Primary Drinking Water Regulations - Maximum Contaminant Level Goals (MCLGs)
U.S. - Colorado - Primary Drinking Water Regulations - Maximum Contaminant Levels (MCLs)
U.S. - Connecticut - Drinking Water Quality Standards - Maximum Contaminant Levels
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)
U.S. - Connecticut - Water Quality Standards - Consumption of Organisms Only
U.S. - Connecticut - Water Quality Standards - Consumption of Water and Organisms
U.S. - Connecticut - Water Quality Standards - Health Designations
U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities
U.S. - Florida - Drinking Water Standards - Volatile Organic Contaminants - Maximum Contaminant Levels (MCLs)
U.S. - Georgia - Drinking Water - Maximum Contaminant Levels (MCLs)
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)
U.S. - Idaho - Occupational Exposure Limits - TWAs
U.S. - Illinois - Toxic Air Contaminant Carcinogens
U.S. - Illinois - Toxic Air Contaminants
U.S. - Louisiana - Reportable Quantity List for Pollutants
U.S. - Maine - Air Pollutants - Hazardous Air Pollutants
U.S. - Maine - Chemicals of High Concern
U.S. - Maryland - Surface Water Quality Standards - Consumption of Organisms Only
U.S. - Maryland - Surface Water Quality Standards - Consumption of Water and Organisms
U.S. - Massachusetts - Allowable Ambient Limits (AALs)
U.S. - Massachusetts - Allowable Threshold Concentrations (ATCs)
U.S. - Massachusetts - Drinking Water - Maximum Contaminant Levels (MCLs)
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2
U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2
RTK - U.S. - Massachusetts - Right To Know List
U.S. - Massachusetts - Threshold Effects Exposure Limits (TELEs)
U.S. - Massachusetts - Toxics Use Reduction Act
U.S. - Michigan - Occupational Exposure Limits - STELs
U.S. - Michigan - Occupational Exposure Limits - TWAs

U.S. - Michigan - Polluting Materials List
U.S. - Minnesota - Chemicals of High Concern
U.S. - Minnesota - Groundwater Health Risk Limits
U.S. - Minnesota - Hazardous Substance List
U.S. - Minnesota - Permissible Exposure Limits - STELs
U.S. - Minnesota - Permissible Exposure Limits - TWAs
U.S. - Missouri - Drinking Water - Maximum Contaminant Levels (MCLs)
U.S. - Nebraska - Drinking Water - Maximum Contaminant Levels (MCLs)
U.S. - New Hampshire - Drinking Water - Maximum Contaminant Levels (MCLs)
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual
U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances
U.S. - New Jersey - Environmental Hazardous Substances List
U.S. - New Jersey - Primary Drinking Water Standards - Maximum Contaminant Levels - MCLs
RTK - U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New Jersey - Special Health Hazards Substances List
U.S. - New Jersey - Water Quality - Ground Water Quality Criteria
U.S. - New Jersey - Water Quality - Practical Quantitation Levels (PQLs)
U.S. - New Mexico - Water Quality - Standards for Ground Water of 10,000 mg/L TDS Concentration or Less
U.S. - New York - Occupational Exposure Limits - TWAs
U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 1-Hour
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour
U.S. - North Dakota - Air Pollutants - Unit Risk Factors
U.S. - North Dakota - Water Quality Standards - Human Health Value for Class III
U.S. - North Dakota - Water Quality Standards - Human Health Value for Classes I, IA, II
U.S. - Oregon - Permissible Exposure Limits - TWAs
U.S. - California - Safer Consumer Products - Initial List of Candidate Chemicals and Chemical Groups
U.S. - Pennsylvania - Drinking Water - Maximum Contaminant Levels (MCLs)
RTK - U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
RTK - U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - 1-Hour
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - 24-Hour
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - Annual
U.S. - Rhode Island - Water Quality Standards - Acute Freshwater Aquatic Life Criteria
U.S. - Rhode Island - Water Quality Standards - Chronic Freshwater Aquatic Life Criteria
U.S. - Rhode Island - Water Quality Standards - Human Health Criteria for Consumption of Aquatic Organisms Only
U.S. - Rhode Island - Water Quality Standards - Human Health Criteria for Consumption of Water and Aquatic Organisms
U.S. - South Carolina - Maximum Contaminant Levels (MCLs)
U.S. - South Carolina - Toxic Air Pollutants - Maximum Allowable Concentrations
U.S. - South Carolina - Toxic Air Pollutants - Pollutant Categories
U.S. - Tennessee - Occupational Exposure Limits - STELs
U.S. - Tennessee - Occupational Exposure Limits - TWAs
U.S. - Texas - Drinking Water Standards - Maximum Contaminant Levels (MCLs)
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term
U.S. - Utah - Drinking Water - Maximum Contaminant Levels (MCLs)
U.S. - Vermont - Permissible Exposure Limits - STELs
U.S. - Vermont - Permissible Exposure Limits - TWAs
U.S. - Virginia - Water Quality Standards - Public Water Supply Effluent Limits
U.S. - Virginia - Water Quality Standards - Surface Waters Not Used for the Public Water Supply Effluent Limits
U.S. - Washington - Permissible Exposure Limits - STELs
U.S. - Washington - Permissible Exposure Limits - TWAs
U.S. - West Virginia - Water Quality - Groundwater Standards - Ceiling Concentrations



Pro Color Finish Resin Safety Data Sheet

U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 25 Feet to Less Than 40 Feet
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 40 Feet to Less Than 75 Feet
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 75 Feet or Greater
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights Less Than 25 Feet

Propylene glycol monomethyl ether acetate (108-65-6)

U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term

n-Butyl acetate (123-86-4)

U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)
U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)
U.S. - Idaho - Occupational Exposure Limits - TWAs
U.S. - Louisiana - Reportable Quantity List for Pollutants
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2
U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2
RTK - U.S. - Massachusetts - Right To Know List
U.S. - Massachusetts - Toxics Use Reduction Act
U.S. - Michigan - Occupational Exposure Limits - STELs
U.S. - Michigan - Occupational Exposure Limits - TWAs
U.S. - Michigan - Polluting Materials List
U.S. - Minnesota - Hazardous Substance List
U.S. - Minnesota - Permissible Exposure Limits - STELs
U.S. - Minnesota - Permissible Exposure Limits - TWAs
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual
U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances
RTK - U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New Jersey - Special Health Hazards Substances List
U.S. - New York - Occupational Exposure Limits - TWAs
U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 1-Hour
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour
U.S. - Oregon - Permissible Exposure Limits - TWAs
RTK - U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
RTK - U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Tennessee - Occupational Exposure Limits - STELs
U.S. - Tennessee - Occupational Exposure Limits - TWAs
U.S. - Texas - City of Austin - Aerosol Paint and Glue Restrictions
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term
U.S. - Vermont - Permissible Exposure Limits - STELs
U.S. - Vermont - Permissible Exposure Limits - TWAs
U.S. - Washington - Permissible Exposure Limits - STELs
U.S. - Washington - Permissible Exposure Limits - TWAs

Iron oxide (Fe₂O₃) (1309-37-1)

U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)

U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)
U.S. - Idaho - Occupational Exposure Limits - TWAs
RTK - U.S. - Massachusetts - Right To Know List
U.S. - Michigan - Occupational Exposure Limits - TWAs
U.S. - Minnesota - Hazardous Substance List
U.S. - Minnesota - Permissible Exposure Limits - TWAs
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual
RTK - U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New York - Occupational Exposure Limits - TWAs
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour
U.S. - Oregon - Permissible Exposure Limits - TWAs
RTK - U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Tennessee - Occupational Exposure Limits - TWAs
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term
U.S. - Vermont - Permissible Exposure Limits - TWAs
U.S. - Washington - Permissible Exposure Limits - STELs
U.S. - Washington - Permissible Exposure Limits - TWAs
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 25 Feet to Less Than 40 Feet
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 40 Feet to Less Than 75 Feet
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 75 Feet or Greater
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights Less Than 25 Feet

Xylenes (o-, m-, p- isomers) (1330-20-7)

U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Acute
U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Chronic
U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728)
U.S. - Colorado - Groundwater Quality Standards
U.S. - Colorado - Hazardous Wastes - Discarded Chemical Products, Off-Specification Species, Container and Spill Residues
U.S. - Colorado - Primary Drinking Water Regulations - Maximum Contaminant Level Goals (MCLGs)
U.S. - Colorado - Primary Drinking Water Regulations - Maximum Contaminant Levels (MCLs)
U.S. - Connecticut - Drinking Water Quality Standards - Maximum Contaminant Levels
U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities
U.S. - Florida - Drinking Water Standards - Volatile Organic Contaminants - Maximum Contaminant Levels (MCLs)
U.S. - Georgia - Drinking Water - Maximum Contaminant Levels (MCLs)
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)
U.S. - Idaho - Occupational Exposure Limits - TWAs
U.S. - Illinois - Toxic Air Contaminants
U.S. - Louisiana - Reportable Quantity List for Pollutants
U.S. - Maine - Air Pollutants - Hazardous Air Pollutants
U.S. - Massachusetts - Allowable Ambient Limits (AALs)
U.S. - Massachusetts - Allowable Threshold Concentrations (ATCs)
U.S. - Massachusetts - Drinking Water - Maximum Contaminant Levels (MCLs)
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2
U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2
RTK - U.S. - Massachusetts - Right To Know List
U.S. - Massachusetts - Threshold Effects Exposure Limits (TELEs)
U.S. - Massachusetts - Toxics Use Reduction Act



Pro Color Finish Resin Safety Data Sheet

U.S. - Michigan - Occupational Exposure Limits - STELS
U.S. - Michigan - Occupational Exposure Limits - TWAs
U.S. - Michigan - Polluting Materials List
U.S. - Minnesota - Chemicals of High Concern
U.S. - Minnesota - Groundwater Health Risk Limits
U.S. - Minnesota - Hazardous Substance List
U.S. - Minnesota - Permissible Exposure Limits - STELS
U.S. - Minnesota - Permissible Exposure Limits - TWAs
U.S. - Missouri - Drinking Water - Maximum Contaminant Levels (MCLs)
U.S. - Nebraska - Drinking Water - Maximum Contaminant Levels (MCLs)
U.S. - New Hampshire - Drinking Water - Maximum Contaminant Levels (MCLs)
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual
U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances
U.S. - New Jersey - Environmental Hazardous Substances List
U.S. - New Jersey - Primary Drinking Water Standards - Maximum Contaminant Levels - MCLs
RTK - U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New Jersey - Special Health Hazards Substances List
U.S. - New Jersey - Water Quality - Ground Water Quality Criteria
U.S. - New Jersey - Water Quality - Practical Quantitation Levels (PQLs)
U.S. - New Mexico - Water Quality - Standards for Ground Water of 10,000 mg/L TDS Concentration or Less
U.S. - New York - Occupational Exposure Limits - TWAs
U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances
U.S. - North Carolina - Control of Toxic Air Pollutants
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 1-Hour
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour
U.S. - North Dakota - Hazardous Wastes - Discarded Chemical Products, Off-Specification Species, Container and Spill Residues
U.S. - North Dakota - Water Quality Standards - Human Health Value for Classes I, IA, II
U.S. - Oregon - Permissible Exposure Limits - TWAs
U.S. - California - Safer Consumer Products - Initial List of Candidate Chemicals and Chemical Groups
U.S. - Pennsylvania - Drinking Water - Maximum Contaminant Levels (MCLs)
RTK - U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
RTK - U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - 1-Hour
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - 24-Hour
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - Annual
U.S. - Rhode Island - Water Quality Standards - Acute Freshwater Aquatic Life Criteria
U.S. - Rhode Island - Water Quality Standards - Chronic Freshwater Aquatic Life Criteria
U.S. - South Carolina - Maximum Contaminant Levels (MCLs)
U.S. - South Carolina - Toxic Air Pollutants - Maximum Allowable Concentrations
U.S. - South Carolina - Toxic Air Pollutants - Pollutant Categories
U.S. - Tennessee - Occupational Exposure Limits - STELS
U.S. - Tennessee - Occupational Exposure Limits - TWAs
U.S. - Texas - City of Austin - Aerosol Paint and Glue Restrictions
U.S. - Texas - Drinking Water Standards - Maximum Contaminant Levels (MCLs)
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term
U.S. - Utah - Drinking Water - Maximum Contaminant Levels (MCLs)
U.S. - Washington - Dangerous Waste - Discarded Chemical Products List
U.S. - Washington - Permissible Exposure Limits - STELS
U.S. - Washington - Permissible Exposure Limits - TWAs
U.S. - West Virginia - Water Quality - Groundwater Standards - Ceiling Concentrations
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 25 Feet to Less Than 40 Feet
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 40 Feet to Less Than 75 Feet

U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 75 Feet or Greater
 U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights Less Than 25 Feet

Titanium dioxide (13463-67-7)

U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)
 U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)
 U.S. - Idaho - Occupational Exposure Limits - TWAs
 U.S. - Illinois - Toxic Air Contaminant Carcinogens
 RTK - U.S. - Massachusetts - Right To Know List
 U.S. - Michigan - Occupational Exposure Limits - TWAs
 U.S. - Minnesota - Chemicals of High Concern
 U.S. - Minnesota - Hazardous Substance List
 U.S. - Minnesota - Permissible Exposure Limits - TWAs
 U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
 U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual
 RTK - U.S. - New Jersey - Right to Know Hazardous Substance List
 U.S. - New York - Occupational Exposure Limits - TWAs
 U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour
 U.S. - Oregon - Permissible Exposure Limits - TWAs
 RTK - U.S. - Pennsylvania - RTK (Right to Know) List
 U.S. - Tennessee - Occupational Exposure Limits - TWAs
 U.S. - Texas - Effects Screening Levels - Long Term
 U.S. - Texas - Effects Screening Levels - Short Term
 U.S. - Vermont - Permissible Exposure Limits - TWAs
 U.S. - Washington - Permissible Exposure Limits - STELs
 U.S. - Washington - Permissible Exposure Limits - TWAs

Aluminum hydroxide (Al(OH)3) (21645-51-2)

U.S. - Texas - Effects Screening Levels - Long Term
 U.S. - Texas - Effects Screening Levels - Short Term


Butyl methacrylate (97-88-1)

U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1
 U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2
 U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity
 U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1
 U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2
 RTK - U.S. - Massachusetts - Right To Know List
 RTK - U.S. - New Jersey - Right to Know Hazardous Substance List
 U.S. - New Jersey - Special Health Hazards Substances List
 RTK - U.S. - Pennsylvania - RTK (Right to Know) List
 U.S. - Texas - Effects Screening Levels - Long Term
 U.S. - Texas - Effects Screening Levels - Short Term

Canadian Regulations

Pro Color Finish Resin

WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	--



2-Propanol, 1,1'-[(4-methylphenyl)imino]bis- (38668-48-3)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
Methyl methacrylate (80-62-6)	
Listed on the Canadian DSL (Domestic Substances List)	
Listed on the Canadian IDL (Ingredient Disclosure List)	
IDL Concentration 1 %	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
2-Ethylhexyl acrylate (103-11-7)	
Listed on the Canadian DSL (Domestic Substances List)	
Listed on the Canadian IDL (Ingredient Disclosure List)	
IDL Concentration 1 %	
WHMIS Classification	Class B Division 3 - Combustible Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects
2,2,4-Trimethyl-1,3-pentanediol diisobutyrate (6846-50-0)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria
Ethylbenzene (100-41-4)	
Listed on the Canadian DSL (Domestic Substances List)	
Listed on the Canadian IDL (Ingredient Disclosure List)	
IDL Concentration 0.1 %	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
Propylene glycol monomethyl ether acetate (108-65-6)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class B Division 3 - Combustible Liquid
2-Propenoic acid, 2-methyl-, oxybis(2,1-ethanediyl) ester (109-17-1)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects
n-Butyl acetate (123-86-4)	
Listed on the Canadian DSL (Domestic Substances List)	
Listed on the Canadian IDL (Ingredient Disclosure List)	
IDL Concentration 1 %	
WHMIS Classification	Class B Division 2 - Flammable Liquid
Iron oxide (Fe₂O₃) (1309-37-1)	
Listed on the Canadian DSL (Domestic Substances List)	
Listed on the Canadian IDL (Ingredient Disclosure List)	
IDL Concentration 1 %	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria
2-Hydroxy-4-methoxybenzophenone (131-57-7)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria
Xylenes (o-, m-, p- isomers) (1330-20-7)	
Listed on the Canadian DSL (Domestic Substances List)	



Pro Color Finish Resin

Safety Data Sheet

WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	--

Titanium dioxide (13463-67-7)

Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects

Aluminum hydroxide (Al(OH)3) (21645-51-2)

Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria

Butyl methacrylate (97-88-1)

Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date : 1/24/2018
Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Acute Tox. 2 (Oral)	Acute toxicity (oral) Category 2
Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Asp. Tox. 1	Aspiration hazard Category 1
Carc. 2	Carcinogenicity Category 2
Comb. Dust	Combustible Dust
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Eye Irrit. 2B	Serious eye damage/eye irritation Category 2B
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 3	Flammable liquids Category 3
Flam. Liq. 4	Flammable liquids Category 4
Repr. 1B	Reproductive toxicity Category 1B
Resp. Sens. 1	Respiratory sensitisation Category 1
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization Category 1
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H227	Combustible liquid
H232	May form combustible dust concentrations in air



Pro Color Finish Resin Safety Data Sheet

H300	Fatal if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H320	Causes eye irritation
H332	Harmful if inhaled
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H351	Suspected of causing cancer
H360	May damage fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

Party Responsible for the Preparation of This Document

Todd Franks

Siplast, Inc.

1111 Highway 67 South

Arkadelphia, AR 71923

870-246-8095 x 1108

ussds@icopal.com

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

North America GHS US 2012 & WHMIS