

Safety Data Sheet acc. to OSHA HCS

Revision Number 8

Revision Date 4/13/2023

1 Identification

- **Product identifier**
- **Product name:** SFT H Membrane Adhesive
- **Relevant identified uses of the substance or mixture.** Elastomeric Urethane Adhesive
- **Application of the substance / the mixture** Elastomeric Urethane Adhesive
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Siplast, Inc.
14911 Quorum Drive, Ste. 600
Dallas, TX 75254
Information Phone Number: 1-800-922-8800
- **Information department:** Global Regulatory Department.
- **Emergency telephone number:**
ChemTrec: Day or Night within USA and Canada: 1-800-424-9300.
Outside USA and Canada: +1 703-527-3887 (collect calls accepted)

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Carc. 2 H351 Suspected of causing cancer.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS07



GHS08

- **Signal word** Danger
- **Hazard statements**
Causes skin irritation.

(Contd. on page 2)

USA

Safety Data Sheet

acc. to OSHA HCS

Revision Number 8

Revision Date 04/13/2023

Product name: SFT H Membrane Adhesive

(Contd. of page 1)

Causes serious eye irritation.
 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 May cause an allergic skin reaction.
 Suspected of causing cancer.
 May cause respiratory irritation.
 May cause damage to organs through prolonged or repeated exposure.

· **Precautionary statements**

Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.
 Do not breathe dust/fume/gas/mist/vapors/spray.
 Wash thoroughly after handling.
 Use only outdoors or in a well-ventilated area.
 Contaminated work clothing must not be allowed out of the workplace.
 Wear protective gloves/protective clothing/eye protection/face protection.
 [In case of inadequate ventilation] wear respiratory protection.
 If on skin: Wash with plenty of water.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
 Continue rinsing.
 IF exposed or concerned: Get medical advice/attention.
 Call a poison center/doctor if you feel unwell.
 Specific treatment (see on this label).
 Get medical advice/attention if you feel unwell.
 Take off contaminated clothing and wash it before reuse.
 If skin irritation or rash occurs: Get medical advice/attention.
 If eye irritation persists: Get medical advice/attention.
 If experiencing respiratory symptoms: Call a poison center/doctor.
 Wash contaminated clothing before reuse.
 Store in a well-ventilated place. Keep container tightly closed.
 Store locked up.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



· **Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture: consisting of the following components.

(Contd. on page 3)

USA

Safety Data Sheet

acc. to OSHA HCS

Revision Number 8

Revision Date 4/13/2023

Product name: SFT H Membrane Adhesive

(Contd. of page 2)

· Hazardous components:

8052-42-4	Asphalt	25-50%
39420-98-9	Isocyanates, Reaction product of polyol with Methylenediphenyl diisocyanate	5-20%
4083-64-1	4-isocyanatosulphonyltoluene	≤0.5%

4 First-aid measures

· Description of first aid measures

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

Call a doctor immediately.

Overexposure, remove to fresh air and seek medical attention.

· After skin contact:

Wash contaminated skin with soap and water.

Immediately wash with water and soap and rinse thoroughly.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Rinse out mouth with water. Drink 1 - 2 glasses of water but DO NOT induce vomiting. Do not give liquids to a drowsy, convulsing or unconscious person. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

Seek medical treatment.

· Information for doctor:

· Most important symptoms and effects, both acute and delayed No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents:

CO₂, extinguishing powder or water spray. Fight larger fires with water spray.

Use fire fighting measures that suit the environment.

· Special hazards arising from the substance or mixture No further relevant information available.

· Advice for firefighters

· Protective equipment: Protective clothing and respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

· Environmental precautions: Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste in accordance with federal state and local regulations.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

(Contd. on page 4)

USA

Safety Data Sheet

acc. to OSHA HCS

Revision Number 8

Revision Date 4/13/2023

Product name: SFT H Membrane Adhesive

(Contd. of page 2)

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:		
8052-42-4	Asphalt	30 mg/m ³
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	9.3 mg/m ³
· PAC-2:		
8052-42-4	Asphalt	330 mg/m ³
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	100 mg/m ³
· PAC-3:		
8052-42-4	Asphalt	2,000 mg/m ³
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	230 mg/m ³

7 Handling and storage

· Handling:

· Precautions for safe handling

Avoid prolonged or repeated contact with skin.

Avoid contact with eyes.

Wash thoroughly after handling.

Prevent formation of aerosols.

· Information about protection against explosions and fires: No special measures required.

· Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles: No special requirements.

· Information about storage in one common storage facility: Store away from oxidizing agents.

· Further information about storage conditions: Keep receptacle tightly sealed.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

8052-42-4 Asphalt	
REL	Ceiling limit value: 5* mg/m ³ *15-min; See Pocket Guide App. A
TLV	Long-term value: 0.5* mg/m ³ *inh. fraction; as benzene-soluble aerosol; BEIp
· Ingredients with biological limit values:	
8052-42-4 Asphalt	
BEI	- Medium: urine Time: end of shift at end of workweek Parameter: 1-Hydroxypyrene with hydrolysis (nonquantitative)

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Revision Number 8

Revision Date 4/13/2023

Product name: SFT H Membrane Adhesive

(Contd. of page 4)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment (see listings below)**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

Not necessary if room is well-ventilated.

In the absence of adequate ventilation, use NIOSH-certified respiratory protection when chemical exposure is excessive or above an established exposure limit. Comply with OSHA 29 CFR 1910.134.

Use approved respiratory protection equipment when airborne exposure is excessive. Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations specified by the manufacturer.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

Nitrile rubber, NBR

Chloroprene rubber, CR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Safety glasses with side shields.



Tightly sealed goggles

· **Body protection:** Protective work clothing

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Mastic

Color: Black

· **Odor:** Faint Petroleum

· **Odor threshold:** Not determined.

(Contd. on page 6)

USA

Safety Data Sheet

acc. to OSHA HCS

Revision Number 8

Revision Date 04/13/2023

Product name: SFT H Membrane Adhesive

(Contd. of page 5)

· pH-value:	Not determined.
· Change in condition	
Melting point:	Undetermined.
Boiling point:	Undetermined
· Flash point:	149 °C (300.2 °F)
· Flammability (solid, gaseous):	Not applicable.
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Flammable limits:	
Lower:	Not determined
Upper:	Not determined
· Vapor pressure:	Not determined.
· Specific gravity at 20 °C (68 °F):	0.98 g/cm ³ (8.1781 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	0.0 %
· Other information	Viscosity: 15,000 - 40,000 cps VOC's < 250 g/l

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** Exposure to high temperatures.
- **Incompatible materials:** Reacts with oxidizing agents.
- **Hazardous decomposition products:**
Oxides of carbon and nitrogen.
Isocyanate
Hydrocarbons
- **Additional information:** AVOID EXPOSURE TO AIR OR MOISTURE UNTIL READY TO USE.

USA

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Revision Number 8

Revision Date 04/13/2023

Product name: SFT H Membrane Adhesive

(Contd. of page 5)

11 Toxicological information

· **Information on toxicological effects**

· **Acute toxicity:**

· **Primary irritant effect:**

· **on the skin:**

May irritate the skin.

Irritant to skin and mucous membranes.

· **on the eye:** Irritating effect.

· **Sensitization:**

Inhalation - Sensitization possible through inhalation.

Skin Contact - Sensitization possible through skin contact.

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

8052-42-4	Asphalt	2B
39420-98-9	Isocyanates, Reaction product of polyol with Methylenediphenyl diisocyanate	3

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:** No further relevant information available.

· **Persistence and degradability:** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential:** No further relevant information available.

· **Mobility in soil:** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

At present there are no ecotoxicological assessments.

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects:** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Must be specially treated adhering to official regulations.

(Contd. on page 8)

USA

Safety Data Sheet

acc. to OSHA HCS

Revision Number 8

Revision Date 4/13/2023

Product name: SFT H Membrane Adhesive

(Contd. of page 7)

Disposal must be made according to official regulations.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **UN-Number**

· DOT, ADN, IMDG, IATA not regulated

· **UN proper shipping name**

· DOT, ADN, IMDG, IATA not regulated

· **Transport hazard class(es)**

· DOT, ADN, IMDG, IATA

· Class not regulated

· **Packing group**

· DOT, IMDG, IATA not regulated

· **Environmental hazards:** Not applicable.

· **Special precautions for user** Not applicable.

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:** DOT, ADR, IMDG, IATA - Not regulated in transport.

· **UN "Model Regulation":** not regulated

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· Sara

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

Substance is listed.

39420-98-9 | Isocyanates, Reaction product of polyol with Methylenediphenyl diisocyanate

· **TSCA (Toxic Substances Control Act):**

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

· **Proposition 65**

Please contact H.B. Fuller for more information regarding Proposition 65 on this product:
reg.request@hbfuller.com .

· **(DSL) Canada Domestic Substance List**

All components of this product are on the DSL(Canada Domestic Substance list) or are exempt from DSL requirements.

· **New Jersey Right-to-Know List:**

8052-42-4 | Asphalt

· **New Jersey Special Hazardous Substance List:**

None of the ingredients is listed.

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Revision Number 8

Revision Date 4/13/2023

Product name: SFT H Membrane Adhesive

(Contd. of page 8)

· **Pennsylvania Right-to-Know List:**

8052-42-4	Asphalt
-----------	---------

· **Pennsylvania Special Hazardous Substance List:**

None of the ingredients is listed.

· **Cancerogenity categories**

· **EPA (Environmental Protection Agency)**

39420-98-9	Isocyanates, Reaction product of polyol with Methylenediphenyl diisocyanate	CBD
------------	---	-----

· **TLV (Threshold Limit Value established by ACGIH)**

8052-42-4	Asphalt	A4
-----------	---------	----

· **MAK (German Maximum Workplace Concentration)**

8052-42-4	Asphalt	2
39420-98-9	Isocyanates, Reaction product of polyol with Methylenediphenyl diisocyanate	4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

8052-42-4	Asphalt
-----------	---------

· **National regulations:**

- **Water hazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

Although the information and recommendations set forth in this SDS are presented in good faith and are believed to be correct as of the date of this SDS, Siplast makes no representations as to the completeness or accuracy thereof. Information is supplied on the condition that the persons receiving and using it will make their own determination as to the suitability for their purpose prior to use. In no event will Siplast or any affiliate thereof be responsible for damages of any nature whatsoever resulting from the use or reliance on the information set forth in the SDS.

· **Department issuing SDS:**

Global Regulatory Department.
ussds@siplast.com

· **Creation Date:** 09/10/2013

· **Date of preparation / last revision** 4/13/2023

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 ICAO: International Civil Aviation Organisation
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 ACGIH: American Conference of Governmental Industrial Hygienists
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 NIOSH: National Institute for Occupational Safety
 OSHA: Occupational Safety & Health
 TLV: Threshold Limit Value
 PEL: Permissible Exposure Limit
 REL: Recommended Exposure Limit
 BEI: Biological Exposure Limit

(Contd. on page 10)

USA

Safety Data Sheet
acc. to OSHA HCS

Revision Number 8

Revision Date 4/13/2023

Product name: SFT H Membrane Adhesive

(Contd. of page 9)

*Skin Irrit. 2: Skin corrosion/irritation – Category 2**Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A**Resp. Sens. 1: Respiratory sensitisation – Category 1**Skin Sens. 1: Skin sensitisation – Category 1**Carc. 2: Carcinogenicity – Category 2**STOT SE 3: Specific target organ toxicity (single exposure) – Category 3**STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2*

USA